

# MILLWORK CATALOG

**WINDOWS** 



# TABLE OF CONTENTS

**PELLA®** 

RESERVE™	KRESTMARK®
WOOD & ALUMINUM CLAD WOOD FAMILIES	6 200-275 VINYL SERIES 76
TRADITIONAL - WOOD & ALUMINUM CLAD WOOD	8 250 VINYL SERIES 78
CONTEMPORARY - ALUMINUM-CLAD WOOD	10 400 VINYL SERIES 80
FEATURES & OPTIONS	12 220 VINYL REPLACEMENT 82
LIFESTYLE SERIES	PLYGEM®
ALUMINUM-CLAD WOOD WINDOWS	16 PLIGEWI
FEATURES & OPTIONS	18 PLYGEM®
	1100 VINYL SERIES 86
IMPERVIA® FIBERGLASS WINDOWS	4800 THERMAL BREAK ALUMINUM 88
FEATURES & OPTIONS	24
FEATURES & OPTIONS	BURRIS WINDOWS
250 SERIES	BURRIS WINDOWS
VINYL WINDOWS	TECTVIEW EX VINYL 92
ENCOMPASS	TECTVIEW AC VINYL
VINYL WINDOWS	
250 SERIES & ENCOMPASS	WINDOR WINDOWS
FEATURES & OPTIONS	32 2750 FOLDING WINDOW
PELLA®	SIMONTON® WINDOWS AND DOORS
WINDOW & PATIO DOOR LINES	
WINDOW & DOOR TRIM OPTIONS	
STEADY SET™	
MI® WINDOWS AND DOORS	PREMIUM VINYL SUNROOM WINDOWS 104
	VELUX®
MI® WINDOWS AND DOORS	
V2000 VINYL MODELS 1255 + 3500	
V2000 VINYL MODEL 3540	
V2000 VINYL MODEL 1555	
V3000 VINYL MODEL 1620	
V3000 VINYL MODEL 1556	
V3000 VINYL MODELS 1675 + 9770	
V3000 VINYL GARDEN WINDOW	
ATRIUM®	COMPLETE LIGHT CONTROL 119
AIRIUM	QPF SELF-FLASHED FIXED SKYLIGHT 120
ATRIUM <sup>®</sup>	FX DOUBLE DOME SKYLIGHT
5700 VINYL SERIES 6	60 QX DOUBLE DOME SKYLIGHT 123
5700 VINYL SLIDER 6	61
130 VINYL SERIES 6	62
150 VINYL SERIES	63
450 VINYL SERIES6	64
750 VINYL SERIES	65
VINYL ARCHITECTURAL SHAPES	66
SIMULATED DIVIDED LITE	
BRONZE LAMINATE	
BLACK PAINT	72

**KRESTMARK®** 





## **WOOD & ALUMINUM CLAD WOOD FAMILIES**



# Pella® Reserve®

Authentic designs with uncompromised attention to detail.


Made for the distinction creators, the purists of design, the architectural historians — each window and door is meticulously designed to achieve your vision. We deliver tailor-made solutions and intentional innovations to achieve your unique vision without concessions. From simple yet sophisticated style to historical detailing, anything less simply won't do.



Pella Reserve — Traditional windows and patio doors are exquisitely designed with unparalleled historical detailing. They feature through-stile construction, deliberate proportions and intricate profiles to achieve authentic traditional style.



## **WOOD & ALUMINUM CLAD WOOD FAMILIES**



Contemporary-designed Pella Reserve windows and patio doors offer simple and sophisticated styles with expansive glass, sleek, minimal profiles and through-stile construction, which embody the tenets of pure contemporary design.

## TRADITIONAL - WOOD & ALUMINUM CLAD WOOD



# Pella® Reserve® Traditional

Wood & Aluminum-Clad Wood

# Unparalleled historical detailing

Featuring historic elements with uncompromised attention to detail, including Integral Light Technology® grilles and a historic putty profile.

# Authentic hardware

With a historically authentic spoonlock and our Antiek casement window hardware inspired by period furniture.

#### Integrated Rolscreen

A retractable screen that appears when you open the window and disappears into the frame when the window is closed.



Exquisitely designed windows and doors with unparalleled historical detailing. Featuring through-stile construction, deliberate proportions and intricate profiles to achieve authentic traditional style. Durable interiors and extruded aluminum exteriors allow you to create the ideal look for your design. And with cutting-edge innovations that solve modern-day inconveniences without compromising the design, your clients can be proud to own Pella Reserve – Traditional windows and patio doors. We know your reputation matters, so we stand behind Pella Reserve products with the best limited lifetime warranty for wood windows and patio doors.\*

Achieve your vision and impress your clients. From preliminary drawings to installation, Pella's expert team of architects, engineers, drafters and consultants can work to deliver custom window and door solutions for your project. Partner with Pella to achieve your unique vision without concessions. And with large multi-slide and bifold patio doors, you can create a space that blurs the lines between indoors and out.

Based on comparing written limited warranties of leading national wood window and wood patio door brands. See Pella written Limited Warranty for details, including exceptions and limitations, at pella.com/warranty or contact Pella Customer Service at 877-473-5527.



## **TRADITIONAL - WOOD & ALUMINUM CLAD WOOD**

Pella Reserve Traditional





#### **Historic elements**

Putty profile. Further your aesthetic with the putty profile, recreated with historically accurate angles to provide meaningful depth and a realistic shadow. These products offer the industry's deepest sash dimension.

**Through-stile construction.** Essential to the tradition of window making, butt joinery and through-stile construction create authentic proportions and emulate historic window design.

Integral Light Technology. Pella's Integral Light Technology helps capture the look of true-dividedlight without sacrificing energy performance.

#### Intentional innovations


#### Single- and double-hung Integrated Rolscreen.

The Integrated Rolscreen is a screen on a single- and double-hung window that appears when you open the window, and rolls away, out of sight, when you close it.

**Innovative sash lugs.** Add sash lugs to the exterior of our double-hung windows to create an authentic look, while maintaining modern tilting functionality for easy cleaning.

**Integrated security sensors.** Preserve the beauty of Pella Reserve windows and doors while protecting what matters most.

Available in these window and patio door styles:



## **CONTEMPORARY - ALUMINUM-CLAD WOOD**



# **Pella® Reserve®**Contemporary

Aluminum-Clad Wood

#### Clean lines

Add sleek, clean lines to your project with industry-leading modern designs.

# 90° exterior profiles

Pella's patented cladding system delivers a clean sash joint with pure, 90-degree exteriors.

#### Modern hardware

Our renowned, exclusive hardware features sleek lines. The Saldo foldaway crank adds the perfect finishing touch.



Achieve your unique design vision without concessions with simple and sophisticated designs. With expansive glass, sleek, minimal profiles and through-stile construction, this design embodies the tenets of pure contemporary style.

With uncompromised attention to detail, our cutting-edge innovations solve modernday inconveniences. Add an expansive multi-slide or bifold patio door to your design for a space that blurs the lines between indoors and out. Preserve the beauty of Pella Reserve – Contemporary windows and doors while protecting what matters most with integrated security sensors. Windows and patio doors can be monitored from virtually anywhere with the free Pella Insynctive® App.¹ And we stand behind our products with the best limited lifetime warranty for wood windows and patio doors.²

<sup>1</sup> Requires the Pella Insynctive App on a smart device, an Insynctive Bridge and a wireless home internet router with internet connection

<sup>&</sup>lt;sup>2</sup> Based on comparing written limited warranties of leading national wood window and wood patio door brands. See Pella written Limited Warranty for details, including exceptions and limitations, at pella.com/warranty or contact Pella Customer Service at 877-473-5527.



## **CONTEMPORARY - ALUMINUM-CLAD WOOD**

**Pella Reserve** Contemporary







#### **Clean lines**

**Expansive glass.** Expansive glass combined with some of the narrowest sightlines in the industry allow you to bring your vision to life.

Minimal profiles. Our industry leading modern design delivers sleek, squared-off sash profiles. Square grille profiles provide another layer of design flexibility.

**Modern hardware.** Our renowned, exclusive hardware has set the bar for the industry. Featuring sleek lines, the Saldo foldaway crank adds the perfect finishing touch.

### **Achieve your vision**

**Durable, extruded aluminum.** Available in a wide variety of exterior colors or create your own unique exterior color to meet your design needs.

**Virtually unlimited customization.** From extra tall to extra wide. Custom sizes, grille patterns and designs, finishes, wood types and glass options are available.

**Tailor-made solutions.** From preliminary drawings to installation, Pella's expert team of architects, engineers, drafters and consultants can work to deliver custom window and door solutions for your project.

Available in these window and patio door styles:



## **FEATURES & OPTIONS**



#### **Colors & Finishes**

Wood Types СТ

Choose the wood species that best complements your project's interior.













**Prefinished** Pine Interior Colors

СТ

When you select pine, we can prefinish in your choice of a variety of paint and stain colors. Unfinished or primed and ready-to-paint are also available.

















Stain

Red Mahogany Stain



Stain



Extruded Aluminum-Clad **Exterior Colors** 

СТ

Our low-maintenance EnduraClad® exterior finish resists chalking and fading. Take durability further with EnduraClad Plus protective finish, which meets the industry's highest exterior coating standard to defend against chalking and fading.<sup>1</sup> Custom colors are also available.













Satin Steel



Matte Gray



Wolf Gray





Sage



Frost Blue







InsulShield® Low-E Glass<sup>2</sup>



Soft Linen

Advanced Low-E insulating dual-pane glass with argon or triple-pane glass with argon<sup>3</sup> СТ



AdvancedComfort Low-E insulating dual-pane glass with argon СТ



NaturalSun Low-E insulating dual-pane glass with argon or triplepane glass with argon<sup>3</sup>



Spice Red

NaturalSun+ Low-E insulating dual-pane glass with argon СТ



СТ

SunDefense<sup>3</sup> Low-E insulating dual-pane glass with argon or triple pane glass with argon



Blue Ash

SunDefense+ Low-E insulating dual-p glass with argon

**Additional Glass Options** 




Laminated (non-impact-resistant)<sup>4,5</sup>, tinted<sup>2,4</sup> or obscure<sup>2,4</sup>



improved dual-pane sound glass<sup>3,6</sup>



СТ



- 1 The highest exterior coating standard for painted aluminum exteriors is the AAMA 2605 standard. EnduraClad Plus protective finish is not available with all colors. See your local Pella sales representative for availability <sup>2</sup> Optional high-altitude InsulShield Low-E glass is available with or without argon on select products.
- Available on select products only. See your local Pella sales representative for availability.
   Available with Low-E insulating glass with argon on select products.
- <sup>5</sup> For best performance, the laminated glass may be in the interior or exterior pane of the insulating glass, depending on the product.
- <sup>6</sup> Sound control glass consists of dissimilar glass thickness (3mm/5mm).



### **FEATURES & OPTIONS**

#### **Grilles**

Grille Types

Choose the look of true divided light with Integral Light Technology® or make cleaning easier by selecting grillesbetween-the-glass.



Ogee Integral Light Technology® 7/8", 1-1/4" or 2"<sup>6</sup>




Square Integral Light Technology\* 5/8", 7/8", 1-1/4" or 2"<sup>6</sup>



Glass 3/4"



**Putty Glaze Integral** Light Technology® with Ogee Interior¹ 5/8", 7/8", 1-1/4" or 2"

















Grille **Patterns** 

In addition to the patterns shown here, custom grille patterns are available.







T



T



C T

Rolscreen soft-closing retractable screens roll out of sight when not in use on Pella Reserve - Traditional casement windows

and sliding patio doors and on Pella Reserve - Contemporary sliding patio doors. The Integrated Rolscreen is a fully





СТ



C T



C T



T





T



Rolscreen® & Integrated Rolscreen



concealed Rolscreen that moves seamlessly with the sash — appearing when you open a Pella Reserve – Traditional single- or double-hung window and rolling completely away when you close it.

Flat C T InView™ screens let in 14% more light and are 8% more open for improved airflow.4

### **Added Peace of Mind**

Integrated Security Sensors

Optional integrated wireless security sensors maintain aesthetics, streamline security installation and ensure no warranty loss is caused by post-installation drilling. Sensors can be monitored via the free Pella® Insynctive® App and are compatible with major security panel systems.<sup>5</sup> For more information, go to connectpella.com.



- Color-matched to your product's interior and exterior color.
- Appearance of exterior grille color may vary depending on the Low-E insulating glass selection
- Warning: Use caution when children or pets are around open windows and doors Screens are not designed to retain children or pets.
   Improved airflow is based on calculated screen cloth openness. Screen cloth transmittance was measured using an integrated sphere spectrophotometer.
- <sup>5</sup> Requires the Insynctive App on a smart device, an Insynctive Bridge and a wireless home router with internet connection

## **FEATURES & OPTIONS**



#### Window Hardware

Classic Collection

T

Get a timeless look with authentic styles in classic finishes.



Fold-Away Crank Antiek



Spoon-Style Lock

#### Finishes:









Matte Black

Oil-Rubbed Bronze

Satin Nickel

in

atin

Satin Brass

Modern Collection Achieve the ultimate contemporary look with exclusive hardware designed by Pella.

С



Fold-Away Crank











Oil-Rubbed Bronze



Polished Chrome

Satin Brass

Rustic Collection

Create a distinct and charming look with distressed finishes.





Fold-Away Crank Antiek



Spoon-Style Lock

Finishes:







Essential

Select from popular designs and finishes to suit every style.





Fold-Away



Cam-Action Lock

Finishes:











Satin Nickel





## **FEATURES & OPTIONS**

#### **Patio Door Hardware**

#### Classic Collection C T

BALDWIN

Choose timeless pieces for a look that will never go out of style.



Hinged & Bifold Patio Door Handles Virago



Sliding & Multi-Slide Patio Door Handle



Multi-Slide Patio Door Handle<sup>1,2</sup>

Finishes:









Modern Collection СТ

BALDWIN

Achieve the ultimate contemporary look with sleek finishes.



Hinged & Bifold Patio Door Handle



Sliding & Multi-Slide Patio Door Handle



Patio Door

Finishes:





Polished



Rustic Collection

BALDWIN

Stand out with bold looks and create an utterly unique aesthetic.



Hinged & Bifold Patio Door Handles



Sliding & Multi-Slide Patio Door Handle Notus

Finishes:







Essential Collection СТ

Elevate your style and transform a home with elegant selections.



Hinged & Bifold Patio Door Handles



**Sliding Patio** 



Multi-Slide Patio Door Handle<sup>1,2</sup>













<sup>&</sup>lt;sup>1</sup> Flush multi-slide handle is a Pella exclusive design.

<sup>&</sup>lt;sup>2</sup> Flush multi-slide handle is not available in Champagne

## **ALUMINUM-CLAD WOOD WINDOWS**



# Pella<sup>®</sup> Lifestyle Series

Aluminum-Clad Wood

#### #1 performing wood window and patio door<sup>1</sup>

For the combination of energy, sound and value.

# 37 time-tested innovations

Create unique, room-by-room solutions to meet real-life needs.

# 83% more energy efficient<sup>2</sup>

On average compared to single-pane windows — with performance solutions for improved comfort.



Create solutions that are perfect for real life. Covered by the best limited lifetime warranty in the industry for wood windows and patio doors, Pella Lifestyle Series offers everything you love about wood — including beauty, durability and style flexibility. $^3$  Begin with dual- or triple-pane glass and then select from the most desired features and options. $^4$ 

Pella Lifestyle Series is the #1 performing wood window and patio door for the combination of energy, sound and value. Packed with purposeful innovations like the Hidden Screen and integrated blinds, shades and security sensors, we designed windows and patio doors to work for your project, room by room.



## **ALUMINUM-CLAD WOOD WINDOWS**

Pella Lifestyle Series







### **Exceptional performance and style.**

Style flexibility. Whether your client's home is traditional, modern or somewhere in between, choose beautiful windows and patio doors that fit their style.

Redefining performance. Get both unrivaled energy efficiency and sound performance at an incredible value. With the Ultimate Performance package, windows are on average 79% more energy efficient and reduce 52% more outside noise than single-pane windows 2,5

Enhanced durability. Our windows are designed to stand the test of time with exterior wood parts treated with exclusive EnduraGuard® wood protection and an aluminum-clad exterior with EnduraClad® finish.

#### Room-by-room solutions.

Hidden Screen. The innovative double-hung screen appears when the window is open and folds away when it is closed. It is easy to install and retrofittable.

Integrated blinds and shades. Intentionally designed to be accessible, blinds and shades are tucked between glass panes and are protected from dust, pets and little hands.

Added security and convenience. Add peace of mind with optional built-in window and door sensors and motorized between-the-glass blinds and shades that raise and lower with a touch of a button.

#### Available in these window and patio door styles:



Performance solutions require upgrades to triple-pane, AdvancedComfort Low-E and mixed glass thickness. Based on comparing product quotes and published STC/OITC and U-Factor ratings of leading national wood window and pa

window and patio door brands.

Window energy efficiency calculated in a computer simulation using RESFEN 6.0 default parameters for a 2000 sq. foot new construction single-story home when comparing Pella Lifestyle Series windows with Advanced Comfort Low-E triple-pane glass with argon and mixed glass thickness to a single pane word or vinyl window. Double-hung windows are not available with triple-pane glass. The energy efficiency and actual savings will vary by location. The average window energy efficiency is based on a national average of 94 modeled critics across the country and weighting based on population. For more details see pella.com/methodology.

<sup>&</sup>lt;sup>3</sup> Based on comparing written limited warranties of leading national wood window and wood patio door brands See Pella written Limited Warranty for details, including exceptions and limitations, at pella.com/warranty, or contact Pella Customer Service at 866-319-0397.

<sup>4</sup> Double-hung window only available with dual-pane glass.

Reduction in sound based on OITC ratings of Pella Lifestyle Series windows with triple-pane glass with mixed glass thickness to a single-pane wood or vinyl window with an OITC of 19. Calculated by using the sound transmission loss values in the 80 to 4000 Hz range as measured in accordance with ASTM E-90(09). Actual results may vary.

## **FEATURES & OPTIONS**



#### **Colors & Finishes**

#### **Wood Type**

A beautiful wood species to complement a home's interior.



Pine

#### Prefinished Pine Interior Colors

We can prefinish in your choice of a variety of beautiful paints and stains. Unfinished or primed and ready-to-paint are













Aluminum-Clad Exterior Colors

Our low-maintenance EnduraClad® exterior finish resists fading and helps protect windows and patio doors for years.



























#### Glass<sup>1</sup>

#### InsulShield® Low-E Glass²



Advanced Low-E insulating dual-pan glass with argon or triple-pane glass with argon



AdvancedComfort Low-E insulating dual-pane glass with argon and triple-pane glass with argon



NaturalSun Low-E insulating dual-pane glass with argon or triple-pane glass with argon



NaturalSun+ Low-E insulating dual- or triple-pane glass with argon



SunDefense Low-E insulating dual-pane glass with argon or triple-pane glass



SunDefense+ Low-E insulating dual- or triple-pane glass with argon

#### Additional Glass Options



Tempered glass available on dual- and triple-pane products



Obscure and frosted obscure glass available on dualand triple-pane products

<sup>&</sup>lt;sup>1</sup> Double-hung window available with dual-pane glass only.

Optional high-altitude Low-E insulating glass does not contain argon in most products. Please see your local Pella sales representative for more information.



## **FEATURES & OPTIONS**

#### **Performance Packages**

To make things easier, we've created performance packages that highlight what's most important to your customers.

Performance solutions offer an unbeatable combination of energy efficiency, sound control and value.¹ Upgrade from a dual-to a triple-pane glass design with the packages below to meet the unique needs of each room in your customer's home.

All values below are averages compared with single-pane windows.



#### **Performance**

Improved energy efficiency and sound performance.

71%

More Energy Efficient<sup>2</sup> 34%

Noise Reduction<sup>3</sup>



#### **Sound Control**

Exceptional noise control for a quieter home.

52%

Noise

Reduction<sup>3</sup>



#### **Energy Efficiency**

Superior energy efficiency for a more comfortable home.

83%

More Energy Efficient<sup>2</sup>



#### **Ultimate Performance**

The best combination of energy efficiency and noise control.

79%

More Energy Efficient<sup>2</sup> 52%

Noise Reduction<sup>3</sup>



Scan the QR code with your smartphone camera to learn more about how each performance package can benefit your client's home.

<sup>1</sup> Performance solutions require upgrades to triple-pane, AdvancedComfort Low-E and mixed glazing thickness glass. Based on comparing product quotes and published STC/OITC and U-Factor ratings of leading national wood window and patio door brands.

<sup>&</sup>lt;sup>2</sup> Window energy efficiency calculated in a computer simulation using RESFEN 6.0 default parameters for a 2000 sq. foot new construction single-story home when Pella Lifestyle Series windows with the respective performance package are compared to a single-pane wood or vinyl window. The energy efficiency and actual savings will vary by location. The average window energy efficiency is based on a national average of 94 modeled cities across the country and weighting based on population. For more details see pella com/methodology.

<sup>&</sup>lt;sup>3</sup> Reduction in sound based on OITC ratings of Pella Lifestyle Series windows with respective performance package compared to a single-pane wood or vinyl window with an OITC of 19. Calculated by using the sound transmission loss values in the 80 to 4000 Hz range as measured in accordance with ASTM E-90(09). Actual results may vary.

## **FEATURES & OPTIONS**



#### **Grilles**

#### **Grille Types**

Choose the look of true divided light, or make cleaning easier by selecting grilles-between-the-glass.

#### Dual-Pan



Simulated-Divided-Light with Spacer 7/8"



Divided-Light without Spacer 7/8"<sup>1</sup>



Aluminum Grilles-Between-the-Glass 3/4"<sup>2</sup>

#### Triple-Pane:



Aluminum Grilles-Between-The-Glass 3/4"<sup>2</sup>

#### **Grille Patterns**

In addition to the patterns shown here, custom grille patterns are available.



ite



Traditio



Top Rov



Cross



#### Screens<sup>3</sup>

Rolscreen®

Rolscreen soft-closing retractable screens roll out of sight when not in use. Available on casement windows and sliding patio doors.

Hidden

The exclusive, easy-to-use Hidden Screen appears when you open a double-hung window and folds away when the window is closed. It allows 44% more natural light into your home when a window is closed than a standard screen.4

Flat

InView screens are clearer than conventional screens and come standard.



InView™

#### **Added Peace of Mind**

Integrated Security Sensors

Optional integrated wireless security sensors maintain aesthetics, streamline security installation and ensure no warranty loss is caused by post-installation drilling. Sensors can be monitored via the free Pella® Insynctive® App and are compatible with major security panel systems. For more information, go to connectpella.com.

<sup>&</sup>lt;sup>1</sup> Color-matched to your product's interior and exterior color.

<sup>&</sup>lt;sup>2</sup> Appearance of exterior grille color may vary depending on the Low-E insulating glass selection.

<sup>&</sup>lt;sup>3</sup> Warning: Use caution when children or pets are around open windows and doors. Screens are not designed to retain children or pets.

<sup>&</sup>lt;sup>4</sup> Based on calculated screen cloth openness.

<sup>&</sup>lt;sup>5</sup> Requires the Insynctive App on a smart device, an Insynctive Bridge and a wireless home router with internet connection.



## **FEATURES & OPTIONS**

#### **Integrated Blinds & Shades**

#### Integrated Blinds\*

Raise blinds up for an unobstructed view or tilt to let in the right amount of light. Our accessible, integrated blinds are available with or without motorization powered by Pella Insynctive® technology.



#### Integrated Shades\*

Our best integrated fabric shades feature a white exterior fabric for a uniform look from the street. Our accessible, integrated shades are available with or without motorization powered by Pella Insynctive® technology.



#### Haven't landed on the final blind or shade color yet? No problem.

With our patented triple-pane design, your customers can make the decision later in the process. Our triple-pane products come with all of the hardware to add blinds or shades before they arrive to the home or later in the building or remodeling process.



Scan the QR code with your smartphone camera to learn more about our motorized Insynctive blinds and shades.

#### Window Hardware

Essential Collection

Our most popular designs with finishes to suit every style.







#### Patio Door Hardware

Essential Collection

Elevate your style and transform a home with elegant selections.





<sup>\*</sup> Available on triple-pane products only.

## **FIBERGLASS WINDOWS**



# Pella<sup>®</sup> Impervia<sup>®</sup>

**Fiberglass** 

# Unmatched strength & lasting durability

Made from our proprietary fiberglass, the strongest material available for windows and patio doors.<sup>1</sup>

#### Sleek, timeless style

Versatile design elements combined with sleek profiles and clean lines deliver a timeless style.

# Proven performance

Get outstanding resistance to water, wind and outside noises while increasing energy efficiency, security and ease of operation.



Pella Impervia products are engineered to last. Our proprietary fiberglass material provides unmatched strength and lasting durability with sleek, timeless style.<sup>2</sup> And they balance thermal efficiency, scale and value when it matters most.

Don't leave water and structural performance to chance. Tested in extremes and designed for every day, Pella Impervia products are engineered for the rigorous performance requirements of a commercial building and are designed to resist water, wind and outside noises.<sup>3</sup> With nearly 100 years in business, it's rare to come across an application that we haven't already designed a robust installation for. We've got you covered with both products and an installation designed for your exact situation. And whether new construction or window replacement, we have a dedicated team of experts to help with your project.



## **FIBERGLASS WINDOWS**

#### Installation solutions & expertise

Save time and reduce costly callbacks with our exclusive installation methods. It's rare to come across an application that we haven't already solved for.

#### **Tested beyond** requirements

Tested to extremes from -40°F to 180°F, our proprietary fiberglass can handle the most extreme heat and subcold.<sup>2</sup> Our products are tested beyond industry standards to help ensure less maintenance with fewer callbacks.

Pella Impervia



#### Rigorously tested, optimized designs.

100x more impact resistant than Fibrex.4 Pella Impervia products are made from our proprietary fiberglass material and are on average 100x more impact-resistant than Andersen Fibrex, a wood/plastic composite product. You can trust our fiberglass products to stand up to a hammer misfire and other jobsite conditions.

Tested beyond requirements. Tested to extremes from -40°F to 180°F, our proprietary fiberglass can handle the most extreme heat and sub-cold.<sup>2</sup> Our products are tested beyond industry standards to help ensure less maintenance with fewer callbacks.

**ENERGY STAR® certified.** Pella Impervia products offer energy-efficient options that will meet or exceed ENERGY STAR guidelines in all 50 states.

#### Sleek, versatile elements.

**Up-to-date color palette.** Interior and exterior color options to achieve your customer's unique design style, including Black. Our colors are a durable, powder-coat finish which resists chalking and fading.

Revolutionary hardware. Our patented Easy-Slide Operator allows your homeowner to simply slide to open casement and awning windows, without the effort of cranking. Select a complementary or contrasting hardware finish to add interest.

Unique factory mulling. Factory-mulled combinations help save you time on the jobsite. And the superior strength of Pella fiberglass allows you to create larger, unique combinations, made just for your remodel or new construction project.

#### Available in these window and patio door styles:



Pella's proprietary fiberglass material has displayed superior strength over wood, vinyl, aluminum, wood/plastic composites, and other fiberglass materials used by leading national brands in tensile and 3-point bend tests performed in accordance with ASTM D638 and D790 testing standards.

In testing performed in accordance with ASTM testing standards, Pella's fiberglass has displayed superior performance in strength, ability to withstand extreme heat and cold and resistance to dents and scratches. Special shape windows are made from a fiberglass resin material.

Pella Impervia windows and patio doors have a performance grade of LC or higher. For information on product ratings see pella.com/performance Impact testing performance based on testing 10 samples of each material using ASTM D256, Method C.

<sup>&</sup>lt;sup>5</sup> Pella products may not meet ENERGY STAR guidelines in Canada. For more information, contact your local Pella sales representative or go to energystar.gc.ca

## **FEATURES & OPTIONS**



#### **Colors & Finishes**

#### Frame Colors

Our long-lasting powder-coat finish resists chalking and fading so you never need to paint or refinish.

Solid-Color Frame











Dual-Color Frame:



r White Inter with Black Exterior





**Glass & Additional Energy Efficiency Upgrades** 

InsulShield® Low-E Glass²



Advanced Low-E insulating dual- or triple-pane glass with argon



AdvancedComfor Low-E dual-pane glass with argon



NaturalSun Low-E insulating dual- or triplepane glass with argon



NaturalSun+ Low-E insulating dual-pane glass with argon



SunDefense\* Low-E insulating dual- or triple-pane glass with argon



SunDefense+ Low-E insulating dual-pane glass with argon

Additional Glass Options



Bronze-tinted Advanced Low-E insulating glass



Obscure Low-E insulating glass



Tempered glas



Laminated (nonimpact-resistant)<sup>3</sup> or tinted<sup>4</sup>



STC (Sound Transmission Class) dual-pane sound control glass<sup>5</sup>



Triple-pane glass6



Impact-resistar

Foam Insulation Options

Optional foam-insulated frames are available to increase energy efficiency.





## **FEATURES & OPTIONS**

#### **Grilles**

#### Grilles

Grilles are color-matched to the window or patio door interior and exterior frame color.



Between-the-Glass 3/4"7



#### Grille **Patterns**

Choose from one of our standard grille patterns, or create a unique look with custom grille patterns.9











#### Screens\*

## Screen

InView screens let in 14% more light and are 8% more open for improved airflow when compared to the conventional fiberglass screen.11



Dual-color frames are available with a block frame or non-integrated nailing fin.

<sup>&</sup>lt;sup>2</sup> Optional high-altitude Low-E insulating glass available with or without argon on select products.

<sup>&</sup>lt;sup>3</sup> For best performance, the laminated glass may be in the interior or exterior pane of the insulating glass, depending on the product.
<sup>4</sup> Available with Advanced Low-E insulating glass with argon with bronze, gray or green tint on selected products.

Sound control glass consists of dissimilar glass thickness (3mm/5mm or 5mm/3mm).
Available on direct set, awning, casement windows and sliding patio doors.

Appearance of exterior grille color may vary depending on the Low-E insulating glass selection.
 Available on direct set windows only.

 <sup>&</sup>lt;sup>9</sup> Grille patterns offered may vary per product. See specific product information for availability.
 <sup>10</sup> Warning: Screen will not stop child or pet from falling out of window or door. Keep child or pet away from open window or door.

<sup>&</sup>quot; Improved airflow is based on calculated screen cloth openness. Screen cloth transmittance was measured using an integrated sphere spectrophotometer.

## **FEATURES & OPTIONS**



#### Window Hardware

Casement & Awning The patented Easy-Slide Operator is a revolutionary way to operate casement and awning windows. Simply slide to open, without the effort of cranking. With precision venting technology, the window will open to an exact location. Or select the fold-away crank, which folds neatly away against the window frame. Both solutions allow roomside window treatments to hang neatly.







Fold-Away Crank



Sliding, Single-& Double-Hung Pella's cam-action lock pulls the sash against the weatherstripping on single-hung, double-hung and sliding windows for a tighter seal.



Cam-Action Lock





## **FEATURES & OPTIONS**

#### **Patio Door Hardware**

Sliding Patio Door 



Secure Vent Lock

A secure vent lock comes standard on all Pella Impervia sliding doors and provides security in both the closed and venting positions.





Patio Door Blinds\*

Blinds-Betweenthe-Glass Add privacy and complement a home's decor with blinds-between-the-glass. Located between panes of glass, blinds are protected from dust, dirt and damage.



 $<sup>^{\</sup>ast}$  Available on select sizes only. Contact your local Pella representative for more information.

## PELLA® 250 SERIES

## **VINYL WINDOWS**



# Pella<sup>®</sup> 250 Series

Vinyl

# Innovative security and privacy features

Optional security and privacy features on windows and patio doors give your customers more peace of mind.

# 52% stronger frames<sup>1</sup>

Multi-chambered vinyl frames and reinforced sashes are stronger than ordinary vinyl for increased durability.

# 62% more energy efficient<sup>2</sup>

Windows with triple-pane glass create a more comfortable home than windows with single-pane glass.



Pella 250 Series products offer innovative and enhanced security and privacy features for more peace of mind. Our exclusive vinyl formula is performance tested for excellent weathering, durability and color retention. Insulating frame chambers improve energy efficiency and multi-chambered frame designs are 52% stronger than ordinary vinyl.

With innovative and enhanced security and privacy features and our durable and low-maintenance, easy-care vinyl, Pella 250 Series windows and patio doors are a great complement to your project.

<sup>&</sup>lt;sup>1</sup> Based on the force required to bend a window frame profile.

<sup>&</sup>lt;sup>2</sup> Window energy efficiency calculated in a computer simulation using RESFEN 5.0 default parameters for a 2000 sq. foot existing single-story home when comparing a Pella 250 Series vinyl window with InsulShield Advanced Low-E triple pane glass with argon to a single paned wood or vinyl window. The range of energy efficiency will vary from 54% to 77% and will vary by location. Your actual savings will vary. The average window energy efficiency is based on a national average of 94 modeled cities across the country with an adjustment based on population. For more details see pella.com/

<sup>&</sup>lt;sup>3</sup> To achieve a Grade 40 rating on ASTM F842, a test for forced entry excluding glass breakage, the optional footbolt must be installed and engaged.



## PELLA® 250 SERIES

## **VINYL WINDOWS**

Pella 250 Series







#### Strong and Secure Vinyl.

Improved security. The classic sliding patio door with integrated footbolt meets or exceeds the highest industry requirements for forced entry and is our most secure vinyl patio door.<sup>3</sup>

**Unique tamper prevention system.** Doubleand single-hung windows are designed with an interlocking checkrail, steel hardware reinforcement and a unique anti-jar sill.

**Strong vinyl material.** With multi-chambered frames and optional steel reinforced sashes, these frames are 52% stronger than ordinary vinyl, resist warping and twisting and install easily.

#### More of Everything You Love.

Excellent energy efficiency. Multiple insulating air chambers deliver comfort for your customers. Upgraded triple-pane windows are on average 62% more energy efficient than single-pane windows?

**Exclusive vinyl formula.** Using our exclusive fade-resistant formula, Pella's high-grade vinyl is performance-tested for excellent durability and weathering.

**Quality that lasts.** To help ensure our products exceed industry requirements and expectations, we test both the entire window and individual parts for strength and durability.

Available in these window and patio door styles:



Special shapes also available.

# **PELLA® ENCOMPASS**

## **VINYL WINDOWS**



# **Encompass** by Pella®

Vinyl

#### Competitively priced


Easy-care, lowmaintenance vinyl at a price that is easy on the budget.

#### **Energy-efficient** options

Offering solutions to improve comfort and help save on heating and cooling costs.

#### **Backed by Pella**

A leader in the window and door industry and a brand that has been trusted for nearly 100 years.



With Encompass by Pella, you can get windows and patio doors backed by the brand you know and trust, at a price that is easy on the budget.

Featuring low-maintenance, high-grade vinyl frames, these windows are energy efficient and look great for years. Lower heating and cooling costs with energyefficient options that will meet or exceed ENERGY STAR® guidelines in all 50 states.

Some Pella products may not meet ENERGY STAR® guidelines in Canada. For more information, contact your local Pella sales representative or go to energystar.gc.ca.

The Pella Limited Lifetime Warranty is non-prorated, meaning the coverages within the defined warranty periods do not decrease over time. See written limited warranty for details, including exceptions and limitations, at installpella.com/warranties, or contact Pella Customer Service at 866-319-0397.

3 Double-hung window available in East Region only.



## PELLA® ENCOMPASS

## **VINYL WINDOWS**

**Encompass by Pella** 







#### Easy-care vinyl.

**Low-maintenance.** The solid color throughout keeps minor dings and scratches virtually invisible and doesn't require painting.

**More comfortable.** Pella's weather protection system helps protect a home from leaks and drafts.

**Stand the test of time.** Our precision welding process makes a strong and more durable product that resists warping and twisting.

#### Designed to make life easier.

**Easy operation.** Pella's true glide balance system allows single- and double-hung windows to open and close easily and quietly.

**Dust-free grilles and blinds.** Never worry about cleaning between-the glass grilles and blinds. Grilles-between-the-glass are sealed between glass on windows and patio doors and blinds-between-the-glass are sealed between glass on patio doors. This keeps the grilles and blinds safe from dust and damage.

**Limited lifetime warranty.** Backed by one of the best warranties in the business, you can be confident in your selection?

Available in these window and patio door styles:3



## **FEATURES & OPTIONS**



#### **Colors & Finishes**

Frame Colors Create a signature look with solid-color and dual-color frames. Dual-color frames allow your customers to choose a different color for the exterior with a White interior.



#### **Glass & Additional Energy Efficiency Upgrades**

InsulShield® Low-E Glass<sup>2</sup>



250 ENC








Advanced Low-E insulating triple-pane glass with argon



250 ENC





NaturalSun+ Low-E insulating dual-pane glass with argon 250 ENC



SunDefense™ Low-E insulating dual-pane glass with argon<sup>3</sup> 250 ENC



SunDefense+Low-E insulating dual-pane glass with argon



Additional **Glass Options** 



Bronze-tinted Advanced Low-E insulating glass with argon<sup>2</sup> 250



insulating glass 250 ENC



Tempered glass 250 ENC



Triple-pane glass 250

Foam Insulation Options

Optional foam-insulated frames are available to increase energy efficiency.



<sup>&</sup>lt;sup>1</sup> Feature availability varies by location. See local Pella representative for details

<sup>&</sup>lt;sup>2</sup> Optional high-altitude Low-E insulating glass available with or without argon on select products.

 $<sup>^{\</sup>rm 3}\,$  Not available with blinds-between-the-glass on Encompass by Pella sliding patio doors.



## **FEATURES & OPTIONS**

#### Grilles

Grille Types Grilles are color-matched to the window or patio door interior and exterior frame color.







Grilles-Betweenthe-Glass Contour 3/4"<sup>1,2</sup>

250 ENC

Grille Patterns Choose from a variety of grille patterns for the traditional look of divided light.4







Top Sash Only







Custom

#### Screens<sup>5</sup>

Flat Window Screens InView $^{-}$  screens are available on all venting vinyl windows and let in 14% more light and are 8% more open for improved airflow when compared to the conventional fiberglass screen.<sup>6</sup> 250 ENC

Sliding Patio Door Screens Heavy-duty sliding screens come standard on Pella 250 Series sliding patio doors and are optional on Encompass by Pella sliding patio doors.

<sup>&</sup>lt;sup>1</sup> Appearance of exterior grille color may vary depending on the Low-E insulating glass selection.

<sup>&</sup>lt;sup>2</sup> Grilles are not available with blinds-between-the-glass on Encompass by Pella sliding patio doors.

<sup>3</sup> Available on Encompass by Pella products in West region only.

<sup>&</sup>lt;sup>4</sup> Grille patterns offered may vary by product. See specific product information for availability.

<sup>&</sup>lt;sup>5</sup> Warning: Use caution when children or pets are around open windows and doors. Screens are not designed to retain children or pets.

<sup>6</sup> Improved airflow is based on calculated screen cloth openness. Screen cloth transmittance was measured using an integrated sphere spectrophotometer.

## **FEATURES & OPTIONS**



#### Window Hardware

Casement and Awning Folds neatly out of the way so it won't interfere with roomside window treatments. Finishes complement frame colors.



Crank 250



Sliding, Single- and Double-Hung

Pella's cam-action locks push the sashes against the weatherstripping for a tighter seal. Optional AutoLock hardware automatically locks the window when it is shut, simply close the sash and confirm it latches.



Cam-Action Lock









Integrated Sash Lift

Make raising and lowering single- and double-hung window sashes easy with a standard, integrated sash lift.



Window Integrated Sash Lift 250 ENC



Window Limited **Opening Devices**  A vent stop can be engaged or disengaged manually and restricts how far the bottom sash of a double-hung window can open. A window opening control device (WOCD) complies with a safety standard and allows for ventilation, emergency escape and rescue when released. A WOCD automatically limits the sash opening to less than four inches, unless it is intentionally disengaged, enabling the sash to fully open.



Vent Stop



Color-Matched Finishes: 250 ENC



## **FEATURES & OPTIONS**

#### **Patio Door Hardware**

Sliding Patio Door Handle Match the door's exterior color with a color-matched handle or coordinate it with other finishes in a home.





Integrated Flush Footbolt Pella 250 Series classic sliding patio door with integrated flush footbolt is our most secure vinyl patio door.¹ The patent-pending footbolt is flush with the frame, providing secondary venting and locking abilities without compromising beauty.





#### Patio Door Blinds

Blinds-Betweenthe-Glass<sup>2,3</sup> Add privacy and complement your project's decor with blinds-between-the-glass. Located between panes of glass, blinds are protected from dust, pets and damage.



<sup>&</sup>lt;sup>1</sup> To achieve a Grade 40 rating on ASTM F842, a test for forced entry excluding glass breakage, the optional footbolt must be installed and engaged

<sup>&</sup>lt;sup>2</sup> Availability varies by size. See a Pella professional for details

<sup>&</sup>lt;sup>3</sup> Available on dual-pane products only. Not available on sliding patio doors with grilles-between-the-glass.


<sup>4</sup> Only available on 60" x 80" and 72" x 80" doors.



## **WINDOW & PATIO DOOR LINES**



Review our lines and discover your best fit.



#### Window & Patio Door Styles<sup>1</sup>








#### **WINDOW & PATIO DOOR LINES**

For more information on Pella's window and patio door offering, see your local Pella sales representative or visit pellaprodealer.com.














- <sup>1</sup> Additional special shapes also available
- Adultional special require upgrades to triple-pane, AdvancedComfort Low-E and mixed glass thickness. Based on comparing product quotes and published STC/OITC and U-Factor ratings of leading national wood window and patio door brands.
- Double-hung window only available with dual-pane glass.
- dual-pane glass.

  4 Pella's proprietary fiberglass material has displayed superior strength over wood, vinyl, aluminum, wood/plastic composites, and other fiberglass materials used by leading national brands in tensile and 3-point bend tests performed in accordance with ASTM D638 and D790 testing standards.

  5 Double-brune window available in Fast
- Double-hung window available in East Region only.



#### **WINDOW & DOOR TRIM OPTIONS**



#### Interior **Wood Trim**

Dramatically reduce installation time with factory-applied and factory-finished trim. Pella's beautiful trim options provide a vast range of choices that are true to your customer's home architectural style and décor.

 $The trim \ around \ Pella^w \ wood, fiberglass \ or \ vinyl \ windows \ and \ doors \ can \ coordinate \ with \ other \ trim \ on \ your \ project, including$ baseboards, crown molding and chair rails. Optional accessories to coordinate with trim profiles are available.

#### **Wood Types**

Choose the wood species that best complements your project's interior.



Oak

#### Prefinished Pine Interior Colors

Trim is available prefinished in your choice of a variety of paints and stains. Unfinished and ready-to-paint are also available.



#### Interior Trim Styles\*

Choose from several styles of prefinished or unfinished wood interior trim to fit your project including these popular styles. Select trim styles available in Oak.













#### **WINDOW & DOOR TRIM OPTIONS**

EnduraClad® Exterior Trim Add distinctive architectural detail to your project and set off the Pella wood windows and patio doors with style. Our low-maintenance, aluminum-clad exterior trim arrives factory-applied on windows and patio doors to save installation time and costs.

#### Exterior Finish Colors

Our low-maintenance, aluminum EnduraClad® exterior finish resists chalking and fading. Custom colors are also available.



#### Exterior Trim Styles

 $Endura Clad\ exterior\ a luminum\ trim\ is\ available\ in\ five\ standard\ profiles.\ Or\ choose\ a\ custom\ design.$ 











Installation Methods

Pella makes installing windows and doors easy. Multiple installation methods and exclusive features save time and help reduce costly callbacks.

For complete installation instructions and videos, visit installpella.com.



# The Future of Window Installation is Here

Meet the **Pella® Steady Set®** Interior Installation System, the **industry's fastest, most labor efficient** wood window installation system with **uncompromising quality!** The awardwinning system is a safer way to install and is **3.15 times faster** and **utilizes less labor** than standard fin installation methods.<sup>2,3</sup> Plus, it is available at no additional cost.

Available on select new construction Pella Reserve<sup>™</sup> and Pella Lifestyle Series windows.

<sup>&</sup>lt;sup>1</sup> Comparing average install time and plumb/level/square measurements of leading national wood window brands when installed following the manufacturer's standard installation methods for new construction windows.

<sup>&</sup>lt;sup>2</sup> Compared to the average of the leading national wood window brands installation methods for new construction windows when installing standard size window (29x59) into 2nd story application.

<sup>&</sup>lt;sup>3</sup> Compared to leading national wood window brands recommended installation methods for new construction windows





#### STEADY SET™ INSTALLATION SYSTEM





## WINDOWS and DOORS









#### What you can expect

#### ENERGY-EFFICIENCY

Our dual-pane insulated glass helps save on heating and cooling costs while enhancing home comfort.

- In cool weather, it provides outstanding thermal performance to eliminate cold spots near windows.
- In warm weather, insulated glass reduces solar heat gain and minimizes interior glare.

#### CONVENIENCE AND STYLE

- Beveled exterior profile creates a clean, timeless aesthetic
- Surface-mounted, forced-entry-resistant locks provide a stronger, safer seal
- · Full-length lift rail for easy opening and closing
- · Tilt-in bottom sash for easy cleaning
- Optional window operating control device for enhanced safety

By MITER Brands™

V2000 SERIES / MODELS 1255 & 3500



#### **V2000 VINYL MODELS 1255 + 3500**

#### **Engineered to perform**

- · Welded, multi-chamber frame and sash
- · Available frame styles: fin, finless
- · Heavy-duty weatherstripping
- · 2 %" frame depth
- · Available with brickmould accessory and integral J-channel\*
- · Wood extension jambs available for 4 1/16" and 6 1/16" wall depths

#### Min and max sizing



Available in 1/4" increments. DP upgrade required for any unit greater than 84" tall. CHS available on XX, XO, OX, XXX, and XOX configurations.

#### **Energy efficient glass**

Optional tempered glass adds additional strength and obscure or rain glass allows light in while protecting privacy.

GLAZING TYPE	U-VALUE	SHGC	STC
Low-E glass	0.33	0.28	28
Low-E glass with grids	0.33	0.26	28
Argon and Low-E glass	0.29	0.28	28
Argon and Low-E glass with grids	0.29	0.26	28
HP Low-E glass	0.33	0.21	28
HP Low-E glass with grids	0.33	0.19	28
Argon and HP Low-E glass	0.29	0.21	28
Argon and HP Low-E glass with grids	0.29	0.19	28

Note: all values based on standard 3/4" dual-pane insulated glass unit unless noted otherwise

#### Create a customized look

Enhance your home's spaces with a variety finish options and grid configurations.

#### FINISH OPTIONS



#### GRID TYPES







\*J-Channel available on 3500 model only











Build boldly by choosing a range of MI window and door styles with expansive views, contemporary framing and hardware.

miwindows.com/windows/V2000/single-hung

©2024 MI Windows and Doors, LLC. All rights reserved. MI-1255-3500-PDS 724

<sup>†</sup> Clay interior available on products manufactured in Texas only; may only be combined with clay extruded exterior

<sup>‡</sup> Exterior laminate available with white interior only; has a satin finish (matte applies to black paint only)

Exterior paint not available with brickmould









#### What you can expect

#### ENERGY-EFFICIENCY

Our dual-pane insulated glass helps save on heating and cooling costs while enhancing home comfort.

- In cool weather, it provides outstanding thermal performance to eliminate cold spots near windows.
- In warm weather, insulated glass reduces solar heat gain and minimizes interior glare.

#### CONVENIENCE AND STYLE

- Beveled exterior profile creates a clean, timeless aesthetic
- Surface-mounted tilt latches and forced-entryresistant locks provide a stronger, safer seal
- · Full-length lift rail for easy opening and closing
- · Tilt-in bottom sash for easy cleaning
- Optional window operating control device for enhanced safety

By MITER Brands™

V2000 SERIES / MODEL 3540



#### **V2000 VINYL MODEL 3540**

#### **Engineered to perform**

- · Welded, multi-chamber frame and sash
- · Heavy-duty weatherstripping
- $\cdot$  Available frame styles: mounting fin, flange, finless
- · 2 %" frame depth
- · Available with brickmould accessory and integral J-channel
- · Wood extension jambs available for 4 1/16" and 6 1/16" wall depths

#### Min and max sizing

WIE	WIDTH		HEI	GНТ
MIN	мах		MIN	MAX
13"	48"		24"	96"
48"	52"		24"	84"
CON	TINUOUS HEA	AD :	& SILL (CHS)	MAX
Twin (Each Window)	47 3/4"		84	4"
Twin (Overall Unit)	95 <sup>5</sup> /8"		8-	4"
Triple (Each Window)	36"		84	4"
Triple (Overall Unit)	108 1/4"		8-	4"

Available in 1/4" increments. DP upgrade required for any unit greater than 84" tall. CHS available on XX, XO, OX, XXX, and XOX configurations.

#### **Energy efficient glass**

Optional tempered glass adds additional strength and obscure or rain glass allows light in while protecting privacy.

GLAZING TYPE	U-VALUE	SHGC	STC
Low-E glass	0.33	0.28	27
Low-E glass with grids	0.33	0.26	27
Argon and Low-E glass	0.30	0.28	27
Argon and Low-E glass with grids	0.30	0.26	27
HP Low-E glass	0.33	0.21	27
HP Low-E glass with grids	0.33	0.19	27
Argon and HP Low-E glass	0.30	0.21	27
Argon and HP Low-E glass with grids	0.30	0.19	27
Argon and LoĒ <sup>3</sup> -340 glass	0.30	0.15	27
Argon and Lo $\bar{E}^3$ -340 glass with grids	0.30	0.13	27

Note: all values based on standard 3/4" dual-pane insulated glass unit unless noted otherwise









#### Create a customized look

Enhance your home's spaces with a variety finish options and grid configurations.

#### FINISH OPTIONS



#### GRID TYPES



<sup>†</sup> Clay interior available on products manufactured in Texas only; may only be combined with clay extruded exterior



Build boldly by choosing a range of MI window and door styles with expansive views, contemporary framing and hardware.

miwindows.com/windows/V2000/single-hung


©2024 MI Windows and Doors, LLC. All rights reserved. MI-3540-PDS 724

<sup>‡</sup> Exterior laminate available with white interior only; has a satin finish (matte applies to black paint only)

Exterior paint not available with brickmould









#### What you can expect

#### ENERGY EFFICIENCY

Our dual-pane insulated glass helps save on heating and cooling costs while enhancing home comfort.

- In cool weather, it provides outstanding thermal performance to eliminate cold spots near windows.
- In warm weather, insulated glass reduces solar heat gain and minimizes interior glare.

#### CONVENIENCE AND STYLE

- Beveled exterior profile creates a clean, timeless aesthetic
- Dual-opposing, mortised recessed locks create a stronger, safer seal
- $\boldsymbol{\cdot}$  Tilt-in top and bottom sash for easy cleaning
- Push-button vent stops enable ventilation without sacrificing safety and security
- Inverted-coil balances with detent clip provide smooth operation and prevent sash from drifting

By MITER Brands™

V2000 SERIES / MODEL 1555



#### **V2000 VINYL MODEL 1555**

#### **Engineered to perform**

- · Welded, multi-chamber frame and sash
- · Interlocking sash with heavy-duty weatherstripping
- · Metal-reinforced meeting rail
- · True-sloping sill
- · 3 1/4" frame depth
- · Available frame styles: finless, mounting fin
- · Wood extension jambs available for 4 1/16" and 6 1/16" wall depths

#### Min and max sizing

WIDTH			HEI	GНТ
MIN	мах		MIN	MAX
15"	17"		28"	84"
17 1/4"	52"		23 1/2"	60"
CONT	CONTINUOUS HEAD		SILL (CHS)	MAX
Twin (Each Window)	37 ¾"		7	7"
Twin (Overall Unit)	75 5/e"		7	7"
Triple (Each Window)	37 ¾"		7	7"
<b>Triple</b> (Overall Unit)	113 1/2"		7	7"

Available in 1/8" increments. CHS available on XX and XXX configurations. 1555 Picture Window is not available with CHS.

#### **Energy efficient glass**

Optional tempered glass adds additional strength and obscure or rain glass allows light in while protecting privacy.

GLAZING TYPE	U-VALUE	SHGC
Argon and Low-E glass	0.28	0.26
Argon and Low-E glass with grids	0.28	0.23
Argon and Low-E DSB glass	0.28	0.26
Argon and Low-E DSB glass with grids	0.28	0.23
Argon and HP Low-E glass	0.29	0.21
Argon and HP Low-E glass with grids	0.29	0.19
Argon and HP Low-E DSB glass	0.28	0.21
Argon and HP Low-E DSB glass with grids	0.28	0.19

Note: all values based on standard 3/4" dual-pane insulated glass unit unless notes otherwise











Build boldly by choosing a range of MI window and door styles with expansive views, contemporary framing and hardware.

miwindows.com/windows/V2000/double-hung

©2024 MI Windows and Doors, LLC. All rights reserved. MI-1555-PDS 724

#### Create a customized look

Enhance your home's spaces with a variety finish options and grid configurations.

#### FINISH OPTIONS



#### GRID TYPES




Grids-Between-the-Glass

Grids-Between-the-Glass









#### What you can expect

#### ENERGY EFFICIENCY

Our dual-pane insulated glass helps save on heating and cooling costs while enhancing home comfort.

- In cool weather, it provides outstanding thermal performance to eliminate cold spots near windows.
- In warm weather, insulated glass reduces solar heat gain and minimizes interior glare.

#### CONVENIENCE AND STYLE

- $\boldsymbol{\cdot}$  Brickmould exterior profile offers a timeless appeal
- Dual-opposing, mortised recessed locks create a stronger, safer seal
- · Integral lift rail for easy opening and closing
- · Tilt-in bottom sash for easy cleaning
- $\cdot$  Inverted-coil balances provide smooth operation
- Push-button vent stops enable ventilation without sacrificing safety and security
- Optional window operating control device for enhanced safety



#### **V3000 VINYL MODEL 1620**

#### **Engineered to perform**

- · Welded, multi-chamber frame and sash
- · 3 1/4" frame depth
- · Heavy-duty weatherstripping
- · Available frame styles: mounting fin, flange, finless
- Optional StormArmor™ package includes impact-resistant glass with argon, Cardinal Lodz-366, and preserve film to protect the glass until installation is complete
- · Optional DP-50 package

#### Min and max sizing

WIE	отн	HE	ІБНТ		
MIN	MAX	MIN	MAX		
15"	48"	24 1/2"	96"		
48 ½"	52 ½"	24 1/2"	74"		
	WITH STORMARMOR				
23"	52 ½"	24 1/2"	75"		

Available in 1/8" increments.

#### **Energy efficient glass**

Optional tempered glass adds additional strength and obscure or rain glass allows light in while protecting privacy.

GLAZING TYPE	U-VALUE	SHGC	STC
Argon and Low-E glass	0.29	0.30	29
Argon and Low-E glass with grids	0.29	0.27	29
Argon and HP Low-E glass	0.29	0.22	29
Argon and HP Low-E glass with grids	0.29	0.20	29
Impact-resistant laminated glass with argon and Lo $\tilde{E}^3$ -366	0.29	0.22	32
Impact-resistant laminated glass with argon and Lo $\tilde{\mathbb{E}}^3$ -366 with grids	0.29	0.20	32
Impact-resistant laminated glass with argon and $\text{Lo}\bar{E}^3\text{-}340$	0.29	0.14	32
Impact-resistant laminated glass with argon and LoE $^3\mbox{-}340$ with grids	0.29	0.13	32

Note: all values based on standard 3/4" dual-pane or 7/8" impact-resistant insulated glass unit unless noted otherwise

#### Create a customized look

Enhance your home's spaces with a variety finish options and grid configurations.

#### FINISH OPTIONS



‡ Exterior laminate available with white interior only

#### GRID TYPES
















Build boldly by choosing a range of MI window and door styles with expansive views, contemporary framing and hardware.

miwindows.com/V3000









#### What you can expect

#### ENERGY EFFICIENCY

Our dual- and triple-pane insulated glass package options help save on heating and cooling costs while enhancing home comfort.

- In cool weather, it provides outstanding thermal performance to eliminate cold spots near windows.
- In warm weather, insulated glass reduces solar heat gain and minimizes interior glare.

#### CONVENIENCE AND STYLE

- $\boldsymbol{\cdot}$  Beveled exterior profile creates a timeless aesthetic
- Dual-opposing, mortised recessed locks create a stronger, safer seal
- Full FlexScreen<sup>™</sup> with Clarity Screen<sup>™</sup> mesh allows for optimal ventilation without compromising visibility
- True-sloping sill optimizes water drainage and eliminates unsightly weep holes
- · Tilt-in top and bottom sash for easy cleaning
- Push-button vent stops enable ventilation without sacrificing safety and security
- Inverted-coil balances with detent clip provide smooth operation and prevent sash from drifting

By MITER Brands™

V3000 SERIES / MODEL 1556



#### V3000 VINYL MODELS 1556

#### **Engineered to perform**

- · Welded, multi-chamber frame and sash
- · Interlocking sash
- · Metal-reinforced meeting rail
- · Available frame styles: mounting fin, finless
- · 3 1/4" frame depth
- $\cdot$  Wood extension jambs available for 4  $9\!\!/16"$  and 6  $9\!\!/16"$  wall depths
- Optional field-applied drywall returns, exterior brickmould, and factory-applied 3 1/2" flat casing

#### Min and max sizing

WIDTH		HEI	GНТ	
MIN	мах		MIN	MAX
15"	48"		28"	80"
48 1/2"	52 1/2"		24 1/2"	60"
CONT	CONTINUOUS HEAD		SILL (CHS)	MAX
Twin (Each Window)	47 3/4"		7-	4"
Twin (Overall Unit)	95 %"		7-	4"
Triple (Each Window)	37 ¾"		74	4"
Triple (Overall Unit)	113 ½"		74	4"

Available in 1/8" increments. CHS available on XX and XXX configurations.

#### **Energy efficient glass**

Optional tempered glass adds additional strength and obscure or rain glass allows light in while protecting privacy.

GLAZING TYPE	U-VALUE	SHGC	STC
Low-E glass	0.31	0.26	28
Low-E glass with grids	0.31	0.24	28
Argon and Low-E glass	0.28	0.26	28
Argon and Low-E glass with grids	0.28	0.23	28
Argon and Low-E DSB glass	0.28	0.26	30
Argon and Low-E DSB glass with grids	0.28	0.23	30
HP Low-E DSB glass	0.32	0.21	30
HP Low-E DSB glass with grids	0.32	0.19	30
Argon and HP Low-E DSB glass	0.28	0.21	30
Argon and HP Low-E DSB glass with grids	0.28	0.19	30
Argon and Low-E triple-pane glass	0.22	0.22	n/a
Argon and Low-E triple-pane glass with grids	0.23	0.20	n/a

Note: all values based on standard 3/4" dual-pane or 7/8" triple-pane insulated glass unit unless noted otherwise









#### Create a customized look

Enhance your home's spaces with a variety finish options and grid configurations.

#### FINISH OPTIONS



#### GRID TYPES



#### BLINDS-BETWEEN-THE-GLASS



Optional addition to let you control sunlight and privacy without the need for bulky window treatments.

#### SIX COLOR OPTIONS

- WhiteTan
- EspressoSlate gray
- TanSand
- Silver moon
- † Clay interior available on products manufactured in Texas only; may only be combined with clay extruded exterior; not available with foam or triple-pane glass ‡ Woodgrain interior not available with black or clay exterior
- § Blinds-between-the-glass available for dual-pane glass only




Build boldly by choosing a range of MI window and door styles with expansive views, contemporary framing and hardware.

miwindows.com/windows/V3000/double-hung

©2024 MI Windows and Doors, LLC. All rights reserved. MI-1556-PDS 724









#### What you can expect

#### ENERGY EFFICIENCY

Our dual- and triple-pane insulated glass package options help save on heating and cooling costs while enhancing home comfort.

- In cool weather, it provides outstanding thermal performance to eliminate cold spots near windows.
- In warm weather, insulated glass reduces solar heat gain and minimizes interior glare.

#### CONVENIENCE AND STYLE

- Triple weatherstripping for enhanced thermal performance
- Folding operator handle with easy-to-use crank mechanics creates a clean, modern aesthetic and delivers smooth, effortless operation
- $90^{\circ}$  hinge capability provides maximum ventilation and airflow
- Multi-point locking hardware creates a tighter, safer seal
- Low-profile screen tabs result in an unobstructed view and simple screen removal



#### V3000 VINYL MODELS 1675 + 9770

#### **Engineered to perform**

- · Welded, multi-chamber frame and sash
- · 3 1/4" frame depth
- · Available frame styles: finless, flange, mounting fin
- Exterior brickmould and 3 1/2" flat casing available on Model 9770
- · Optional StormArmor™ package includes impact-resistant ∫ glass with argon, Cardinal LoE3-366, and preserve film to protect the glass until installation is complete



 $\cdot$  Wood extension jambs available for 4  $\% _{16}$  and 6  $\% _{16}$  wall depths

#### Min and max sizing

WIE	WIDTH		HEIGHT	
MIN	мах		MIN	MAX
16"	36"		24"	74"
16"	40"		24"	72"
Available in 1/8" inc	rements.			1

#### **Energy efficient glass**

Optional tempered glass adds additional strength and obscure or rain glass allows light in while protecting privacy.

GLAZING TYPE	U-VALUE	SHGC	STC
Argon and Low-E glass	0.25	0.22	28
Argon and Low-E glass with grids	0.25	0.20	28
Argon and HP Low-E glass	0.26	0.18	28
Argon and HP Low-E glass with grids	0.26	0.16	28
Argon and Low-E triple-pane glass*	0.19	0.21	29
Argon and Low-E triple-pane glass with grids*	0.19	0.19	29
Impact-resistant laminated glass with Argon and Lo $\bar{E}^3$ -366	0.25	0.17	n/a
Impact-resistant laminated glass with Argon, Lo $\bar{E}^3$ -366, and grids	0.25	0.16	n/a
Impact-resistant laminated glass with Argon and Lo $\bar{E}^3$ -340	0.26	0.12	n/a
Impact-resistant laminated glass with Argon, Lo $\bar{E}^{3}$ -340, and grids	0.26	0.11	n/a

Note: all values based on standard 3/4" dual-pane or 1-1/8" triple-pane insulated glass unit unless noted otherwise \*Qualifies for ENERGY STAR® Most Efficient tax credit.

- † Clay interior may only be combined with clay extruded exterior; not available with triple-pane glass.
- # Woodgrain interior not available with black or clay exterior; available on 1675 model only.
- § Black interior available with black laminate exterior only.
- fl Exterior laminate available with white interior or black interior; available only on 1675 model.

  \*\* Blinds-between-the-glass available on 1675 model only; for dual-pane glass only; not available with StormArmor.











#### Create a customized look

Enhance your home's spaces with a variety finish options and grid configurations.

#### FINISH OPTIONS



#### GRID TYPES



#### BLINDS-BETWEEN-THE-GLASS"



Optional addition to let you control sunlight and privacy without the need for bulky window treatments.

#### SIX COLOR OPTIONS

- · White • Tan
- · Espresso · Slate gray
- Silver moon
- Sand



Build boldly by choosing a range of MI window and door styles with expansive views, contemporary framing and hardware.

miwindows.com/windows/V3000/casement



#### **V3000 VINYL GARDEN WINDOW**





#### What you can expect

#### ENERGY-EFFICIENCY

Our dual-pane insulated glass helps save on heating and cooling costs while enhancing home comfort.

- In cool weather, it provides outstanding thermal performance to eliminate cold spots near windows.
- In warm weather, insulated glass reduces solar heat gain and minimizes interior glare.

#### CONVENIENCE AND STYLE

- Fully welded PVC vinyl frame provides long-term durability
- Aluminum and steel reinforcements in the front mullion improve structural performance
- Vents and deadlites have a built-in weep system for optimal water drainage
- FlexScreen<sup>™</sup> allows for maximum airflow while keeping pests out
- Inside front-mounted multi-point locks and operators ensure safety and security
- Engineered for new construction and remodeling applications



#### **V3000 VINYL GARDEN WINDOW**

#### **Engineered to perform**

- · Shipped completely assembled and ready to install
- $\cdot$  1" insulated glass unit with dual-pane clear glass
- Top-sloped insulated tempered glass (constant 35° pitch)
- · 1 1/4" exterior grade plywood head board, seat board, and jamb
- Available with adjustable glass shelves and finely-crafted edge banding and knee brace trim
- · Optional Low-E and argon for increased thermal performance

#### Min and max sizing



#### Create a customized look

Enhance your home's spaces with a variety finish options and grid configurations.

#### FINISH OPTIONS

#### VINYL/EXTRUDED FRAME



#### SPECIALTY FRAME COLORS



#### HEAD BOARD, SEAT BOARD, AND JAMB



#### CORIAN SOLD-SURFACE SEAT BOARD



† Champagne and Cocoa available on exterior with white interior only ± Light Oak available on interior with white exterior only













Build boldly by choosing a range of MI window and door styles with expansive views, contemporary framing and hardware.

miwindows.com/V3000





#### **5700 VINYL SERIES**











#### SERIES 5700

#### VINYL SIDE-LOAD SINGLE HUNG WINDOW

- + Removable bottom sash
- + Industry leading air infiltration performance
- + 1 1/4" Nail-fin setback for brick veneer construction and select stucco applications
- Sweep lock helps provide a weather-tight seal and added security
- Dual weather-stripping helps block air and water infiltration, keeping harsh elements outside and energy-saving comfort inside
- + Versatile half screen\* installs easily from inside
- Double insulated glass provides energy saving efficiency. A host of glass options are available, including Low-E coatings and Argon Gas fill for additional efficiency and ENERGY STAR® compliance
- + Sloped sill reduces air infiltration and accommodates easy water run-off
- Multi-chambered vinyl lineals improve thermal performance and enhance sound absorbency

- + Built-in accessory channels accommodate multiple installation options
- + Block and Tackle Balance System for ease of operation
- + Fusion-welded frame and sash minimizes water and air infiltration and enhances overall durability
- Removable operable sash makes cleaning a breeze. Also includes full length interlock and bottom weather stripping
- + Limited lifetime warranty provides reassuring peace of mind
- Pre-punched integral nail-fin targets proper nail location for quick, easy installation
- Modular sized so that rough opening widths for multiple units are easy to calculate:

5700 Single = 35.5" 5700 Twin = 71.5" 5700 Triple = 107.5"

- + DP Rating R50 (window size tested 36" x 96")
- + Jamb depth: 2.625"

#### CUSTOM Options

+ Low-E Glass

+ COLOR

OPTIONS\*

- + Low-E Glass + Argon Gas
- + Ultra Low-E Glass + Argon Gas
- + 5%" or 34" flat, 5%" or 1" contoured, 5%" contoured valance grids available

White

- + Factory mulling of twins, triples and architectural shapes
- + Custom sizes available
- + Safety latch for sash restriction (field applied)
- + Paintable or stainable wood jamb extensions (4 %16" and 6 %16")





www.atrium.c



ENERGY STAR compliance available in all series. Verify product specifics before ordering.







Note: Manufacturer reserves the right to substitute components as necessary for continued product improvemen "Screens are not meant to restrain a child from falling through an open window.

through an open window.
"Printing process may affect color shown. Please refer to actual window sample when selecting colors. REV 2/20 TX





#### **ATRIUM® 5700 VINYL SLIDER**









#### SERIES 5700

#### VINYL HORIZONTAL SLIDING WINDOW

- + 1 1/4" Nail-fin setback for brick veneer construction and select stucco applications
- + Sweep lock helps provide a weather-tight seal and added security
- + Dual weather-stripping helps block air and water infiltration, keeping harsh elements outside and energy-saving comfort inside
- + Versatile half screen\* installs easily from inside
- + Double insulated glass provides energy saving efficiency. A host of glass options are available, including Low-E coatings and Argon gas fill for additional efficiency and ENERGY STAR® compliance
- + Multi-chambered vinyl lineals improve thermal performance and enhance sound absorbency
- + Fusion-welded frame and sash minimizes water and air infiltration and enhances overall durability

#### CUSTOM Options

- + Low-E Glass
- + Low-E Glass + Argon Gas
- + Ultra Low-E Glass + Argon Gas
- + 5/8" or 3/4" flat, 5/8" or 1" contoured, 5/8" contoured valance grids available
- + Custom sizes available
- + Paintable or stainable wood jamb extensions (4 %16" and 6 %16")

- + Metal reinforced meeting rail and sash rail provide added durability and enhanced security
- + Limited lifetime warranty provides reassuring peace of mind
- + Pre-punched integral nail-fin targets proper nail location for quick, easy installation
- + Tandem wheel and axle roller assemblies ensure smooth, easy operation on even the largest sizes
- + Multi-cavity vinyl lineals improve thermal performance and enhance sound absorbency
- (window size tested 72" x 48")





ENERGY STAR compliance available in all series Verify product specifics before ordering.







+ COLOR OPTIONS







Bronze

Note: Manufacturer reserves the right to substitute components as necessary for continued product improvement. 
\*\*Screens are not meant to restaria a child from falling through an open window. 
\*\*Printing process may affect color shown. Please refer to actual window sample when selecting colors. REV 2/20 TX

#### 130 VINYL SERIES











#### SERIES 130 SINGLE HUNG WINDOW

Single hung, slider, picture windows and architectural shapes

- + Bottom sash tilts in for easy cleaning from inside
- + Aluminum half screen comes standard\*
- + Block and tackle balance system for easy sash movement
- + Warm-Edge spacer system provides energy saving thermal performance
- + DP-50 rating (window size tested 53" x 77")
- + Aluminum reinforcement standard in lock & meeting rails and sash stiles
- + Dual Sweep locks (standard at 27 1/4" and above) help provide a weather-tight seal and added security
- + Dual weather-stripping helps block air and water infiltration, keeping harsh elements outside and energy-saving comfort inside
- + Step sill design combines water run-off and aesthetic features of a sloped sill with the structural strength and internal drainage system of a pocket sill
- + Jamb depth: 3"



- CUSTOM Options
- + Low-E Glass
- + Low-E Glass + Argon Gas
- + Ultra Low-E Glass + Argon Gas
- + Non-reflective Low-E Glass and Nonreflective Low-E Glass with Argon Gas
- + 1 1/8" simulated divided lite (SDL) grid

Brick Red\*

Gray'

- + 5/8" or 1" contoured, 5/8" or 3/4" flat,  $\frac{5}{8}$ " contoured valance grids
- + Nine painted exterior colors (white interior only)

- + Charcoal aluminum half screen\*
- + Oriel style

Tan\*\*

+ Window Opening Control Device (WOCD)

Black\*

- + Factory mulling and factory prepared mulling
- + Commodity sizing available
- + Custom sizes available



Step Bevel design creates a beautiful exterior appearance





Select styles and glass packages can be ordered to meet ENERGY STAR® 7 guidelines. See your Atrium Territory







+ FRAME **TYPES** OPTIONS:

+ COLOR OPTIONS'





Bronze\*\*





Terratone\*\*\*

Bronze Laminate

Black

Laminate

You Tube

Note: Manufacturer reserves the right to substitute

Note: Manufacturer reserves the right to substitute components as necessary for continued product improvement. 
"Screens are not meant to restrain a child from falling through an open window.
"Printing process may affect color shown. Please refer to actual window sample when selecting colors. 
"Grid offering limited to 5/8" contoured or SDL on exterior painted windows. Only use mild, water based household cleaner on painted product and rinse immediately with water. 
See full cleaning instructions for details. REV 11/23



#### **150 VINYL SERIES**









#### SERIES 150 SINGLE HUNG WINDOW

Single hung, slider, picture windows and architectural shapes

- + Beautiful, true brick mould exterior frame perimeter
- + Bottom sash tilts in for easy cleaning
- + Fully welded frame and sash corners
- + Sloped sill for easy water run-off
- + DP-50 Rating (window size tested 36" x 74")
- + Integrated J-channel (Series 160 available without J-channel)
- + Pre-punched nail fin makes installation simple
- CUSTOM Options
- + Low-E Glass
- + Low-E Glass + Argon Gas
- + Ultra Low-E Glass + Argon Gas
- + 5/8" or 3/4" flat, 5/8" or 1" contoured, 1 1/8" simulated divided lite (SDL), 5/8" contoured valance grids available
- + Nine painted exterior colors (white interior only)
- + Factory mulling of twins, triples and architectural shapes
- + Paintable or stainable wood jamb extensions (4  $\%_{16}$ " and 6  $\%_{16}$ ")

- + Insulated glass panels with optimum thermal air space featuring warm-edge spacer system
- + Block and tackle balance system
- + Continuous head and sill on twins and triples
- + Half screen comes standard\*
- + Jamb depth: 3.277"
- + Matching slider series 151 available in 2- and 3-lite styles
- + Limited lifetime warranty
- + Exterior 3 1/4" flat casing with Sill Nose DP-35 Rating (window size tested 36" x 74")
- + Charcoal aluminum mesh screen\*
- + Window Opening Control Device (WOCD)
- + Custom sizes available



Brick Mould



Pre-punched nailing fins and integrated



3 1/4" flat casing with sill nose







Dark



Clav

+ EXTERIOR COLOR\*



+ PAINTED EXTERIOR COLOR\*\*



Hunter







Clav\*\*





Select styles and glass packages can be ordered to meet ENERGY STAR® 7 guidelines. See your Atrium Territory Sales Manager for details.







Note: Manufacturer reserves the right to substitute

Note: Manufacturer reserves the right to substitute components as necessary for continued product improvement. "Screens are not meant to restrain a child from falling through an open window." Printing process may affect color shown, Please refer to actual window sample when selecting colors. "Grid offering limited to 5/8" confound or SDL on exterior painted windows. Only use mild, water based household cleaner on painted product and rinse immediately with water. Sae full cleaning instructions for details. BPLS 11/23. See full cleaning instructions for details. REV 11/23

#### **450 VINYL SERIES**











#### SERIES 450 DOUBLE HUNG WINDOW

Double hung, picture windows and architectural shapes

- + Beautiful, true brick mould exterior frame perimeter
- + Both sashes tilt in for easy cleaning
- + Fully welded frame and sash corners
- + Sloped sill for easy water run-off
- + Insulated glass panels with optimum thermal air space featuring warm-edge spacer system
- + DP-35 Rating (available with DP-50 option, window size tested 36" x 74")
- + Series 455/465 available with DP-50 Rating

CUSTOM Options

+ Low-E Glass + Argon Gas

for secure ventilation

+ Ultra Low-E Glass + Argon Gas

+ 5/8" or 3/4" flat, 5/8" or 1" contoured,

1 1/8" simulated divided lite (SDL),

5%" contoured valance grids available

+ Dual push-button night vents

+ Nine painted exterior colors

(white interior only)

+ Low-E Glass

- + Integrated J-channel (Series 460 available without J-channel)
- + Pre-punched nail fin makes installation simple
- + Block and tackle balance system
- + Continuous head and sill on twins and triples
- + Half screen comes standard\*
- + Jamb depth: 3.868"
- + Matching slider #451 available in 2- and 3-lite styles
- + Limited lifetime warranty



#### + Exterior 3 1/4" flat casing with Sill Nose + Factory mulling of twins, triples

- and architectural shapes + Paintable or stainable wood jamb
- extensions (4 %16" and 6 %16")
- + Brass or brushed nickel locks
- + Charcoal aluminum mesh screen\*
- + Window Opening Control Device (WOCD)
- + Custom sizes available



Our New Low Profile Lock



Pre-punched nailing fins and integrated J-channel



+ COLOR OPTIONS\*







Select styles and glass packages can be ordered to meet ENERGY STAR® 7 guidelines. See your Atrium Territory Sales Manager for details.







Note: Manufacturer reserves the right to substitute

- Note: Manufacturer reserves the right to substitute components as necessary for continued product improvement. 
  "Screens are not meant to restrain a child from falling through an open window." 
  "Printing process may affect color shown, Please refer to actual window sample when selecting colors.
  "Grid offering limited to 5/8" contoured or SDL on exterior painted windows. Only use mild, water based household cleaner on painted product and rinse immediately with water. Sae full cleaning instructions for details. BPU 11/23. See full cleaning instructions for details. REV 11/23



#### **750 VINYL SERIES**









#### SERIES 750 CASEMENT WINDOW

Series 755 awning window also available

- + Beautiful, true brick mould exterior frame perimeter
- + Low profile handle folds in and provides a popular aesthetic appeal
- + Narrow profile permits expanded viewing area
- + Fusion-welded frame and sash ensure weather-tight performance
- + Full-perimeter double weather stripping
- + Pre-punched nail fin makes installation
- + Insulated glass panels with optimum thermal air space featuring warm-edge spacer system

- + Concealed hinges and hardware let you open casement windows 90 degrees for better ventilation and easier cleaning
- + Full screens mount on the interior and are removable for easy cleaning\*
- + Tandem locks come standard on all casements over 34" in height
- + Jamb depth: 3.25"
- + Multi-point locking system provides superior pull-in mechanism with single lever
- + Limited Lifetime Warranty



Single vent casement

#### CUSTOM Options

- + Low-E Glass
- + Low-E Glass + Argon Gas
- + Ultra Low-E Glass + Argon Gas
- + 5/8" or 3/4" flat, 5/8" or 1" contoured, 1 1/8" simulated divided lite (SDL), 5/8" contoured valance grids available
- + 2" simulated meeting rail
- + Charcoal aluminum, Clear View and heavy duty screens\*\*
- + Nine painted exterior colors (white interior only)



Brick mould exterior



Low profile handle



Pre-punched nail fin



Single vent awning





Select styles and glass packages can be ordered to meet ENERGY STAR® 7 guidelines. See your Atrium Territory Sales Manager for details.







Note: Manufacturer reserves the right to substitute

Note: Manufacturer reserves the right to substitute components as necessary for continued product improvement. 
"Screens are not meant to restrain a child from falling through an open window.
"Printing process may affect color shown. Please refer to actual window sample when selecting colors. 
"Grid offering limited to 5/8" contoured or SDL on exterior painted windows. Only use mild, water based household cleaner on painted product and rinse immediately with water. 
See full cleaning instructions for details. REV 11/23



#### **VINYL ARCHITECTURAL SHAPES**















**Quarter Round** 

ENGINEERED FOR THAT PERFECT

#### ARCHITECTURAL TOUCH

Create a window system that truly stands out—from octagons and trapezoids to full circles, half rounds, eyebrows and more, we can custom craft any specialty window to fulfill your visions.



Colonial Arch

Operable Eyebrow



Colonial Arch Flanker



Colonial Flanker

- + Standard sizes are available plus a full range of architectural options to accommodate any building style, from colonial to contemporary, from Cape Cod to Southwest
- + Factory mulling is at your calling for quick, hassle-free installation
- + Insulated glass panels with optimum thermal air space featuring a warm-edge spacer system
- + Operable eyebrows and half eyebrows available in Series 150/160 operate sash
- + Optional wood jamb extensions (paintable or stainable pine 4 %16" and 6 %16" available)
- + Limited lifetime warranty



Half Eyebrow







Octagon









Pentagon



**Eyebrow Transom** 





Eyebrow

ARCHITECTURAL SHAPES




#### VINYL ARCHITECTURAL SHAPES

+ Low-E Glass


+ Obscure glass

+ Double strength glass + 5%" or 3¼" flat grid + 5%" or 1" contoured grid

#### **Quarter Round**




#### **Half Round**




#### **Elliptical**




#### **Eyebrow Transom**




#### Eyebrow



#### Colonial Arch




#### Colonial Arch Flanker



#### **Full Round**



#### Oval



#### Octagon



## Triangle

#### Trapezoid

MO & MZ



#### Half Eyebrow



#### Colonial Flanker



#### AVAILABLE OPTIONS FOR

AVAILABLE OPTIONS FOR NEW CONSTRUCTION

+ Low-E Glass + Argon Gas

+ Ultra Low-E Glass + Argon Gas

+ 1 1/8" Simulated Divided Lite grid

(vertical or horizontal only)

+ White, Almond, Clay Vinyl Colors

#### REPLACEMENT


- + Low-E Glass
- + Low-E Glass + Argon Gas (standard on Series 8900 & 8700 only)
- + Ultra Low-E Glass + Argon Gas
- + Obscure glass
- + Double strength glass
- + 5/8" or 3/4" flat grid
- + 5/8" or 1" contoured grid
- + 1 1/8" Simulated Divided Lite grid (Series 8900 and 8700 only; vertical or horizontal only)
- + White, Almond Vinyl Colors
- + Interior Wood Laminates (Series 8900 only; no grid)
- + Exterior Bronze Laminate (Series 8700 only; no grid)
- + Nine Exterior Painted Colors (Series 8900 & 8300 only; no grid)
- + InsulKor Foam Filled Frame (Series 8900 only)
- + Super Spacer nXt Glass (Series 8900 only)
- + Triple Pane Low-E with Argon (Series 8900 only)
- + Triple Pane Ultra Low-E with Argon (Series 8900 only)
- + Decorative Glass (Series 8900 only)
- + Lifetime Glass Breakage Warranty (standard on 8900)

Manufacturer reserves the right to substitute components as necessary. Screens are not meant to restrain a child from falling through an open window.

<sup>\*</sup> Printing process may affect color shown. Please refer to actual window sample when selecting colors

#### VINYL ARCHITECTURAL SHAPES







#### SIMULATED DIVIDED LITE











#### SIMULATED DIVIDED LITE (SDL) GRID

We are proud to offer a traditional simulated divided lite raisedstyle grid on interior and exterior window and door surfaces.

Simulated Divided Lite is available on the following products:

#### Replacement

- + Series 8700 Double Hung
- + Series 8900 Double Hung
- + Series 700 Casement
- + Series 705 Awning

#### New Construction

- + Series 130 Single Hung
- + Series 150 and Series 160 Single Hung
- + Series 450 and Series 460 Double Hung
- + Series 750 Casement
- + Series 755 Awning

#### Patio Doors

+ Series 312 and 332

Also includes picture windows, architectural shapes and sliders of these series.

#### Features

- + A handcrafted look for any home, especially great for use in historical districts
- + Grids are color-matched and affixed permanently to the frame, providing the look of authentic divided lites
- + Grid size: 11/8"
- + One-week delivery





Series 8900 with SDL











Note: Manufacturer reserves the right to substitute components as necessary for continued product improvement. 
\*Printing process may affect color shown. Please refer to actual window sample when selecting colors. 
\*Grid offering limited to 5/8" contoured or SDL on exterior painted windows. Only use mild, water based household cleaner on painted product and rinse immediately with water. 
See full cleaning instructions for details. REV 11/23

A DIVISION OF CORNERSTONE BUILDING BRANDS | SIDING + ACCESSORIES | WINDOWS + DOORS | STONE VENEER | TRIM + MOULDINGS | FENCE + RAILING





#### PROUDLY MADE IN TEXAS



## Bronze. Beautiful and timeless.



Series 5700 shown here

bronze laminate exterior with white interior



The beauty of bronze windows for your home. Our bronze exterior laminate is available on:

#### AVAILABLE ON:

- + Series 5700 New Construction
- + Series 130 New Construction (available on fin only and box frames)
- + Series 8050 Replacement
- + Series 8700 Replacement (also available with contoured grid)

#### AVAILABLE WITH:

- + Single Hung and Picture Window Styles
- + 5/8" flat grid



5%" Flat Grid



5%" or 1" Contoured Grid (exterior view only;

Contact your window representative for more details. The timeless style of bronze.

atrium.com

#### **BLACK PAINT**





### BLACK EXTERIOR PAINT AVAILABLE NOW

Black windows are increasingly popular with homeowners. We are pleased to offer it on these quality Atrium products:

**NEW CONSTRUCTION products:** 

SERIES 450 DOUBLE HUNG (Including 455, 460, 465, 451 & 461)

SERIES 150 SINGLE HUNG (Including 160, 151, 161 & Operable Shapes)

SERIES 130 SINGLE HUNG (Including all Four Frame Types & Operable Shapes)

SERIES 750 CASEMENTS SERIES 755 AWNINGS



SERIES 8900 DOUBLE HUNG (Including Picture Windows and 2 & 3-Lite Sliders)

SERIES 8300 DOUBLE HUNG (Including Picture Windows and 2 & 3-Lite Sliders)

SERIES 700 CASEMENTS SERIES 705 AWNINGS

SERIES 312 & 332 SLIDING PATIO DOORS

\*Not available with 4 panel 12' patio doors







Color options can be purchased via WindowWizard. Available with white interior only.

5/8" contoured and SDL grid option available depending on particular Series. Contact Atrium representative or visit atrium.com for more details.

Note: Manufacturer reserves the right to substitute components as necessary for continued product improvement.

\*\*Printing process may affect color shown. Please refer to actual window sample when selecting colors.

Only use mild, water based household cleaner on painted product and rinse immediately

















# Krestmark®







Series 200 is cleanly designed with a smooth beveled exterior profile giving it a nice bold appearance. Series 275 has a profiled exterior simulating wood brick moulding. Available in Single Hung, Picture Window, Horizontal Slider and Architectural Shapes in White, Sandstone and Clay. Series 200 available in Black/White laminate.

- Multi-chambered, fusion-welded, extruded-vinyl frame and sash provides stability and strength, thermal-resistant properties, and is extremely low maintenance.
- Tilt-in removable bottom sash for ease of cleaning has dual sash locks on units 18" and wider, reducing air infiltration; recessed tilt latches, integral lift rail adds strength.
- Metal reinforced meeting rail for added strength, positive locking and reduced air infiltration.
- Sill features a combined sloped and weep system, ensuring quick and easy water run off.
- Integral pre-punched nail fin adds strength, a weather tight barrier and ease of installation.
- Dual-weatherstrip system reduces infiltration to meet or exceed national testing standards.
- Dual pane 3/4" clear insulated glass with Warm Edge Spacer.
- Block and tackle balances provide smooth operation; locking shoes prevent sash from falling out when tilting for cleaning or removal.




# 200-275 VINYL SERIES

# Krestmark® Collection

### **200 Series** – New Construction

















CLAY

### NFRC PERFORMANCE RATINGS

(3/4" overall IG with Quanex Duralite spacer)

SINGLE	Glass Type Exterior +	Gap	Grid	Perfori	NFRC mance f	Ratings			
HUNG			Option	U-F	SHGC		Southern	S.Central	N.Central
		Air	no Grid	0.33	0.22	0.51	No	No	No
Standard	LoE-366 + Clear	Air	with Grid	0.33	0.20	0.46	No	No	No
Standard		Argon	no Grid	0.30	0.22	0.51	Yes	No	No
		Argon	with Grid	0.30	0.20	0.46	Yes	No	No
STC rated		Air	no Grid	0.33	0.22	0.50	No	No	No
(STC = 29)	LoF-366 +	Air	with Grid	0.33	0.20	0.45	No	No	No
requires DSB + 3/16" glass	Clear	Argon	no Grid	0.29	0.22	0.50	Yes	No	No
thickness		Argon	with Grid	0.29	0.20	0.45	Yes	No	No

HORIZONTAL	Glass Type Exterior +	Gap Fill	Grid	Perfor	NFRC mance f	Ratings	EnergyStar® v7 Climate Zone Compliance			
SLIDER		FIII	Option	U-F	SHGC		Southern	S.Central	N.Central	
		Air	no Grid	0.33	0.22	0.51	No	No	No	
Standard	LoE-366 + Clear	Air	with Grid	0.33	0.20	0.46	No	No	No	
Standard		Argon	no Grid	0.29	0.22	0.51	Yes	No	No	
		Argon	with Grid	0.29	0.20	0.46	Yes	No	No	
STC rated (STC = 29)		Air	no Grid	0.34	0.22	0.51	No	No	No	
requires	LoE-366 +	Air	with Grid	0.35	0.20	0.45	No	No	No	
DSB + 3/16" glass thickness &	Clear	Argon	no Grid	0.29	0.22	0.51	Yes	No	No	
11/16" IG		Argon	with Grid	0.30	0.20	0.45	Yes	No	No	

	PICTURE	Glass Type Exterior +	Gap	Grid Option	Perfor	NFRC mance f	Ratings	En Climate	ergyStar® Zone Con	v7 npliance
	WINDOW				U-F	SHGC		Southern	S.Central	N.Central
			Air	no Grid	0.32	0.23	0.54	Yes	No	No
	Standard	LoE-366 + Clear	Air	with Grid	0.32	0.21	0.49	Yes	No	No
	Standard		Argon	no Grid	0.28	0.23	0.54	Yes	Yes	No
			Argon	with Grid	0.28	0.21	0.49	Yes	Yes	No
STC	rated (STC = 31)		Air	no Grid	0.34	0.24	0.53	No	No	No
	requires	LoE-366 +	Air	with Grid	0.36	0.22	0.48	No	No	No
DS	DSB + 3/16" glass thickness &	Clear	Argon	no Grid	0.29	0.23	0.53	Yes	No	No
	11/16" IG		Argon	with Grid	0.30	0.21	0.48	Yes	No	No

Unless specified, the NFRC values & Energy Star compliance are for double glazed, SSB (3/32") glass thickness. For glass thicknesses above this, contact your sales representative for ratings information.

 $Please\ visit\ Westlake Royal Windows. com\ for\ for\ more\ information.$ 


You may qualify for a tax credit when you replace your existing windows. For more information, go to energystar.gov











The Series 250 casement, awning and picture windows are primarily used for new construction. The actual unit size, however, is ½" under call out and is manufactured in some of the most common sizes used for replacement window installations. For some of these replacement applications the integral nail fin could be removed.

Note: All picture windows, shapes and one-frame glass larger than 30 square feet will come with Tempered Glass as standard for safety reasons. All additional charges for Tempered Glass will automatically be applied.

- Multi-chambered, extruded vinyl frame and sash provide stability with excellent strength, thermal-resistant properties and is extremely low maintenance.
- Fusion-welded corners in frame and sash provides strength and virtually eliminates air and water infiltration.
- Single, twin and triple casements, awnings, picture combinations, 1/4 and 1/2 rounds, arches and eyebrows are available as mulled transoms.
- 3/4" insulated glass, warm-edge spacer, energy-efficient LoE coating option. Type and look of warm edge spacer may vary.
- Multi-point locking hardware with hinged-side snubber, folding handle to minimize window treatment interference, and sash alignment wheel.
- Dual-durometer, double weather strip, energy-efficient system with welded corners for excellent performance and resistance to weather penetration.
- Certifications of all products tested are done to meet or exceed national testing standards by NFRC and AAMA; Energy Star® partner; TDI
- Argon-enhanced glass improves energy efficiency.
- Tempered obscure, bronze or grey glass; 3/4" dual-insulated clear glass.
- Grille patterns: 3/4" Colonial, Prairie, 1" Contoured and 1-1/8" Simulated Divided Lite.
- Factory mulled or stacked units and field mull accessories.



# **250 VINYL SERIES**

# Krestmark® Collection

### **250 Series** – New Construction

### NFRC PERFORMANCE RATINGS

(3/4" overall IG with Quanex Duralite spacer)




CASEMENT	Glass Type Exterior +	Gap	Grid	NFRO	Perforn Ratings		EnergyStar* v7 Climate Zone Compliance		
CASEIVIEIVI	Interior	Filİ	Option	U-F	SHGC		Southern	S.Central	N.Central
	LoE-366 + Clear	Air	no Grid	0.30	0.19	0.43	Yes	No	No
Cr		Air	with Grid	0.30	0.17	0.38	Yes	No	No
Standard		Argon	no Grid	0.27	0.18	0.43	Yes	Yes	No
		Argon	with Grid	0.27	0.17	0.38	Yes	Yes	No

AWNING	Glass Type Exterior +	Gap	Grid	NFRC Performance Ratings			EnergyStar* v7 Climate Zone Compliance		
AWMING	Interior	Fill	Option	U-F	SHGC		Southern	S.Central	N.Central
	LoE-366 + Clear	Air	no Grid	0.30	0.19	0.43	Yes	No	No
Chan dand		Air	with Grid	0.30	0.17	0.38	Yes	No	No
Standard		Argon	no Grid	0.27	0.18	0.43	Yes	Yes	No
		Argon	with Grid	0.27	0.17	0.38	Yes	Yes	No

	PICTURE	Glass Type Exterior +	Gap	Grid	NFRC Performance Ratings			EnergyStar® v7 Climate Zone Compliance		
	WINDOW	Interior	Fill	Option	U-F	SHGC		Southern	S.Central	N.Central
		LoE-366 + Clear	Air	no Grid	0.29	0.22	0.51	Yes	No	No
l	Standard		Air	with Grid	0.29	0.20	0.45	Yes	No	No
ı	Standard		Argon	no Grid	0.26	0.21	0.51	Yes	Yes	No
			Argon	with Grid	0.26	0.19	0.45	Yes	Yes	No

Unless specified, the NFRC values & Energy Star compliance are for double glazed, SSB (3/32") glass thickness. For glass thicknesses above this, contact your sales representative for ratings information.

Please visit WestlakeRoyalWindows.com for more Energy Star options.


















You may qualify for a tax credit when you replace your existing windows. For more information, go to energystar.gov











The 400 Series Window is primarily a new construction window but should not be ruled out for remodeling or replacement applications. Available in Single Hung, Horizontal Slider, Picture Window, architectural shapes and mulled units.

- Multi-chambered extruded vinyl frame and sash provide stability with excellent strength, thermalresistant properties and is extremely low maintenance.
- Integral pre-punched nail fin adds strength, is a weathertight barrier and provides ease of installation.
- Fusion-welded corners in frame and sash provide strength and virtually eliminates air and water infiltration.
- Dual pane 3/4" insulated glass with environmentally friendly Warm Edge Spacer reduces thermal loss (type may vary).
- All picture windows, shapes and one-frame glass larger than 30 square feet will come with Tempered Glass as standard for safety reasons. All additional charges for Tempered Glass will automatically be applied.




# **400 VINYL SERIES**

# Krestmark® Collection

### **400 Series** – New Construction

Argon-enhanced glass improves energy efficiency. E66 is a light green tint and provides the most efficient U-Factor & SHGC.

Tempered, obscure, bronze or grey glass.
Factory mulled or stacked units and field mull accessories.
Impact available for coastal areas, added security or sound dampening (See Series 4000).











### NFRC PERFORMANCE RATINGS

(3/4" overall IG with Quanex Duralite spacer)

SINGLE	Glass Type Exterior +	Gap	Grid	NFRC Po	erformance	Ratings		ergyStar® Zone Con	
HUNG	Interior	Fill	Option	U-F	SHGC	VT	Southern	S.Central	N.Central
		Air	no Grid	0.32	0.23	0.54	Yes	No	No
Standard	LoE-366 + Clear	Air	with Grid	0.32	0.21	0.48	Yes	No	No
Standard		Argon	no Grid	0.28	0.23	0.54	Yes	Yes	No
		Argon	with Grid	0.28	0.21	0.48	Yes	Yes	No
		Air	no Grid	0.34	0.23	0.53	No	No	No
IMPACT rated (Missle-D)	LoE-366	Air	with Grid	0.35	0.21	0.48	No	No	No
Requires DSB	+ Clear	Argon	no Grid	0.29	0.23	0.53	Yes	No	No
+ 6.9L glass		Argon	with Grid	0.30	0.21	0.48	Yes	No	No
STC rated		Air	no Grid	0.34	0.24	0.53	No	No	No
(STC = 32) requires DSB	LoE-366	Air	with Grid	0.35	0.21	0.48	No	No	No
+ 3/16 glass thickness & 11/16" IG	+ Clear	Argon	no Grid	0.29	0.23	0.53	Yes	No	No
	F	Argon	with Grid	0.30	0.21	0.48	Yes	No	No

HORIZONTAL	Glass Type	Gap	Grid Option	NFRC Po	erformance	Ratings	EnergyStar® v7 Climate Zone Compliance		
SLIDER	Exterior + Interior	Filİ		U-F	SHGC	VT	Southern	S.Central	N.Central
		Air	no Grid	0.32	0.23	0.54	Yes	No	No
Considerat	LoE-366 + Clear	Air	with Grid	0.32	0.21	0.48	Yes	No	No
Standard		Argon	no Grid	0.29	0.23	0.54	Yes	No	No
		Argon	with Grid	0.29	0.21	0.48	Yes	No	No
IMPACT		Air	no Grid	0.34	0.23	0.53	No	No	No
	LoE-366	Air	with Grid	0.35	0.21	0.48	No	No	No
	+ Clear	Argon	no Grid	0.29	0.23	0.53	Yes	No	No
		Argon	with Grid	0.30	0.21	0.48	Yes	No	No

PICTURE	Glass Type	Gap	Grid	NFRC Pe	erformance	Ratings		ergyStar® Zone Con	
WINDOW	Exterior + Interior	Filİ	Option	U-F	SHGC		Southern	S.Central	N.Central
	LoE-366 +	Air	no Grid	0.30	0.25	0.59	No	No	No
Standard	Clear		with Grid	0.30	0.23	0.53	Yes	No	No
Standard		Argon	no Grid	0.26	0.25	0.59	No	No	No
			with Grid	0.26	0.23	0.53	Yes	Yes	No
IMPACT rated		Air	no Grid	0.39	0.26	0.56	No	No	No
(Missle-D)	LoE-366 +	Air	with Grid	0.43	0.24	0.51	No	No	No
Requires 3/16"	Clear	Argon	no Grid	0.33	0.26	0.56	No	No	No
+ 8.6L glass		Argon	with Grid	0.36	0.23	0.51	No	No	No
STC rated (STC		Air	no Grid	0.30	0.25	0.58	No	No	No
= 30)	LoE-366 +	Air	with Grid	0.30	0.23	0.52	Yes	No	No
requires DSB + 3/16" glass	Clear	Argon	no Grid	0.26	0.25	0.58	No	No	No
+ 3/16" glass thickness		Argon	with Grid	0.26	0.23	0.52	Yes	Yes	No

Unless specified, the NFRC values & Energy Star compliance are for double glazed, SSB (3/32") glass thickness. For glass thicknesses above this, contact your sales representative for ratings information.

It is recommended not to mix LoE-360 with LoE-366 products within the same building structure since the inward and outward color/shade appearances are noticeably different.

 $Please\ visit\ Westlake Royal Windows. com\ for\ more\ Energy\ Star\ options.$ 

You may qualify for a tax credit when you replace your existing windows. For more information, go to energystar.gov











The Vinyl Replacement Window 220 is offered with a LoE glass option. LoE high performance glass with argon gas allows light to filter in while keeping the sun's harmful rays out. In addition, this special glazing saves energy and reduces utility costs by keeping the cool air inside in the summer and the warm air inside in the winter.

Note: All picture windows, shapes and one-frame glass larger than 30 square feet will come with Tempered Glass as standard for safety reasons. All additional charges for Tempered Glass will automatically be applied.

- 3" main frame beveled exterior profile gives an outstanding, bold appearance.
- Tilt-in sash for easy cleaning.
- Block and tackle balance system for long-lasting, smooth, quiet operation
- 3/4" LoE E66 Environsealed Windows™, environmentally friendly with warm-edge spacer reduces thermal loss. Type and look of warm-edge spacer may vary.
- Ventilation control for opening windows only 4".
- Metal-reinforced center bar for better structural performance and weather tightness.
- Multi-chambered design for structural integrity, superior thermal performance, maintenance-free, vinyl frame and sash extrusions.
- Argon-enhanced glass improves energy efficiency.
- The Replacement 220 is available with an integral nail fin.
- Tempered glass, rain glass, obscure glass.
- Factory mulls (combined units) with continuous head and sill.




# **200 VINYL REPLACEMENT**

# Krestmark® Collection

# **220 Series** – Replacement

# resiliar Collection












**CARDINALIG ♦** 



NFRC PERFORMANCE RATINGS

	SINGLE	Glass Type Exterior +	Gap	Grid	NFRC Performance Ratings			EnergyStar® v7 Climate Zone Compliance		
	HUNG	Interior	Fill	Option	U-F	SHGC		Southern	S.Central	N.Central
			Air	no Grid	0.33	0.22	0.51	No	No	No
	Standard	LoE-366 + Clear	Air	with Grid	0.33	0.20	0.46	No	No	No
	Standard	+ Clear	Argon	no Grid	0.30	0.22	0.51	Yes	No	No
			Argon	with Grid	0.30	0.20	0.46	Yes	No	No
	STC rated		Air	no Grid	0.33	0.22	0.50	No	No	No
	(STC = 29)	LoE-366	Air	with Grid	0.33	0.20	0.45	No	No	No
	requires DSB + 3/16" glass thickness	+ Clear	Argon	no Grid	0.29	0.22	0.50	Yes	No	No
			Argon	with Grid	0.29	0.20	0.45	Yes	No	No

PICTURE	Glass Type Exterior +	Gap	Grid	NFRC	Perforn Ratings		EnergyStar® v7 Climate Zone Compliance			
WINDOW	Interior	Filİ	Option	U-F	SHGC		Southern	S.Central	N.Central	
		Air	no Grid	0.32	0.23	0.54	Yes	No	No	
Standard	LoE-366 + Clear	Air	with Grid	0.32	0.21	0.49	Yes	No	No	
Standard		Argon	no Grid	0.28	0.23	0.54	Yes	Yes	No	
		Argon	with Grid	0.28	0.21	0.49	Yes	Yes	No	
STC rated		Air	no Grid	0.34	0.24	0.53	No	No	No	
(STC = 31) requires DSB +	+ LoE-366 + _ Clear	Air	with Grid	0.36	0.22	0.48	No	No	No	
3/16" glass thickness		Argon	no Grid	0.29	0.23	0.53	Yes	No	No	
& 11/16" IG	Argon	with Grid	0.30	0.21	0.48	Yes	No	No		

	HORIZONTAL	Glass Type Exterior +	Gap	Grid	NFRC Performance Ratings			e EnergyStar® v7 Climate Zone Compliance			
	SLIDER	Interior +	Filİ	Option	U-F	SHGC		Southern	S.Central	N.Central	
			Air	no Grid	0.33	0.22	0.51	No	No	No	
	Standard	LoE-366 + Clear	Air	with Grid	0.33	0.20	0.46	No	No	No	
	Standard		Argon	no Grid	0.29	0.22	0.51	Yes	No	No	
			Argon	with Grid	0.29	0.20	0.46	Yes	No	No	
	STC rated		Air	no Grid	0.34	0.22	0.51	No	No	No	
	(STC = 29) requires DSB +	LoE-366 +	Air	with Grid	0.35	0.20	0.45	No	No	No	
	3/16" glass Clear thickness & 11/16" IG	Clear	Argon	no Grid	0.29	0.22	0.51	Yes	No	No	
			Argon	with Grid	0.30	0.20	0.45	Yes	No	No	

Unless specified, the NFRC values & Energy Star compliance are for double glazed, SSB (3/32") glass thickness. For glass thicknesses above this, contact your sales representative for ratings information.

Please visit WestlakeRoyalWindows.com for more Energy Star options.

You may qualify for a tax credit when you replace your existing windows. For more information, go to energystar.gov










# 1100 VINYL SERIES



# **BUILDER SERIES**

WINDOWS



More value. More performance. More solutions. If you're looking for a window that delivers the best possible performance at the best possible value, look no further than Ply Gem Windows Builder Series. It's energy-efficient and offers a variety of material choices, most of which are virtually maintenance-free and can withstand the toughest tests, including the test of time. Plus, with our service and support you'll be able to get the job done the right way on time and on budget.



# **PLYGEM®**

### 1100 VINYL SERIES



# 1100 SERIES SINGLE HUNG

plygem.com/windows



### **COLOR OPTIONS:**











### **PERFORMANCE:**

PERFORMANCE GRADE			
LC - PG30	48" x 96"		
R - PG40	36" x 96", 44" x 74"		
R - PG45	36" x 74"		
R - PG40	(Twin - 2) 79½" x 65½"		
R - PG35	(Triple -3) 107½" x 71½"		

THERMAL PERFORMANCE							
3MM GLASS	3MM GLASS		NFRC CERTIFIED				
R VALUE		U Factor SHGC VT		VT			
WITH WARM EDGE							
3/4" Low-E	2.86	0.35	0.31	0.55			
3/4" Low-ESC	2.86	0.35	0.23	0.43			
3/4" Low-E2+	3.33	0.3	0.3	0.53			
3/4" Low-E2+SC	3.33	0.3	0.22	0.42			
WITH WARM EDGE+							
¾" HP Glass	3.33	0.3	0.31	0.55			
3/4" HPSC Glass	3.33	0.3	0.22	0.43			
3/4" HP2+ Glass	3.85	0.26	0.3	0.53			
3/4" HP2+SC Glass	3.85	0.26	0.22	0.42			

All units are NAMI certified and rated in accordance with NFRC 100/200 standards by an AAMA accredited lab. Performance values reflect the performance of units tested with the following configuration: 3%" IGU, 3mm glass and no grilles

R VALUE: Restrictive ambient air flow; U FACTOR: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance


NOTE: Colors shown are close approximations and may not be accurate representations for color matching. Please request color swatches from your Ply Gem sales representative to do so.

### STANDARD FEATURES



- Energy-efficient Warm Edge insulating glass
- Maintenance-free multi-chamber PVC construction







- easy cleaningFlush mounted tilt latches
- Traditional brick mould profile with 23/4" frame depth
- Interior glazed top sash, exterior glazed bottom sash
- Aluminum reinforced meeting rail with cam locks that engage keepers for your security
- Block and tackle balances

### **OPTIONS**



### GLASS OPTIONS:

Low-E, Low-E<sup>sc</sup>, Low-E2+, Low-E2+sc, HP, HP<sup>sc</sup>, HP2+, HP2+sc, Warm Edge+ spacer, rain, obscure and tempered



Can be ordered ENERGY STAR® version 7 certified in the South Central and Southern zones.



### **GRILLE OPTIONS:**

Color-coordinated grilles-between-the-glass (GBG) in %" and 34" flat, 13%6" SDL with Shadow Bar



### PRODUCT CONFIGURATIONS:

Singles, twins, triples, fixed, combinations and a wide variety of architectural shapes

### HARDWARE OPTIONS:

Safety vent latch to meet ASTM F2090 requirements, factory installed or prep for field installation

### **SOUND CONTROL OPTIONS:**

STC 24, 27, 31, or 34



© 2024 Ply Gem Windows & Doors, part of Cornerstone Building Brands, Inc. ALL RIGHTS RESERVED. 3751101101187/REVQ/MS/CG/0224

A DIVISION OF CORNERSTONE BUILDING BRANDS





# **4800 THERMAL BREAK ALUMINUM**







# **4800 THERMAL BREAK ALUMINUM**



### **4810 SERIES SINGLE HUNG**





### **4810 SERIES THERMAL PERFORMANCE**

		NFRC CERTIFIED					
	R Value	U Factor	SHGC	VT			
WARM EDGE							
3/4" IGU Clear	1.61	0.62	0.65	0.67			
3/4" IGU Low E	2.08	0.48	0.31	0.57			
3/4" IGU Low E <sup>SC</sup>	2.13	0.47	0.24	0.44			
3/4" IGU Low E 2+	2.33	0.43	0.30	0.55			
3/4" IGU Low E <sup>SC</sup> 2+	2.33	0.43	0.23	0.43			
3/4" IGU HP	2.27	0.44	0.31	0.57			
3/4" IGU HP <sup>sc</sup>	2.27	0.44	0.24	0.44			
3/4" IGU HP 2+	2.50	0.40	0.30	0.55			
3/4" IGU HP <sup>sc</sup> 2+	2.50	0.40	0.23	0.43			
WARM EDGE							
3/4" IGU Low E	2.13	0.47	0.31	0.57			
3/4" IGU Low E <sup>SC</sup>	2.13	0.47	0.24	0.44			
3/4" IGU Low E 2+	2.38	0.42	0.30	0.55			
3/4" IGU Low E <sup>SC</sup> 2+	2.38	0.42	0.23	0.43			
3/4" IGU HP	2.27	0.44	0.31	0.57			
3/4" IGU HPsc	2.33	0.43	0.24	0.44			
3/4" IGU HP 2+	2.50	0.40	0.30	0.55			
3/4" IGU HP <sup>sc</sup> 2+	2.50	0.40	0.23	0.43			

All units are NAMI certified and rated in accordance with NFRC 100/200 standards by an AAMA accredited lab. Performance values reflect the performance of units tested with the following configuration: %" IGU, 3mm glass and no grilles.

R VALUE: Restrictive ambient air flow; U FACTOR: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

- 1. Low E glass options available including solar cooling glass for warm climates.
- 2. Optional HP glass combines Low-E with argon gas fill for high performance.
- 3. Impact Rated units are available in select sizes and configurations.

2019 Ply Gem® Windows & Doors, part of the Cornerstone Building Brands family. All rights reserved. 3751101101192/RevF/MS/CG/1219

### STANDARD FEATURES

- Thermally broken aluminum frame with polyurethane poured in place and debridged to reduce thermal conductivity of aluminum frame
- Virtually maintenance-free extruded aluminum construction with electrostatically applied finish
- Sloped sill allows for proper water drainage to the exterior
- Sleek profile provides larger viewing area
- · Interior glazing allows for easier glass replacemen
- Side load removable bottom sash.
- Block and tackle balance system
- Energy-efficient Warm Edge insulating glass
- Structural meeting rail provides rigid stability and allows for a tighter, weather-resistant unit
- Dual lift rails on bottom sash for easy operation
- Frame depth available in 2½6
- Integral nailing fin with a 1%" setback for simple installation





WARM EDGE TECHNOLOGY

### GLASS OPTIONS:

Low-E, Low-E<sup>SC</sup>, Low-E2+, Low-E<sup>SC</sup>2+, HP, HP<sup>SC</sup>, HP2+, HP<sup>SC</sup>2+, obscure and tempered



Color-coordinated grilles-between-the-glas (GBG) in 5/8", 3/4" flat and 1-3/16" SDL with shadow bar



Matching side lites, fixed panels, transoms, segmented transoms and a wide selection of architectural shapes

### HARDWARE OPTION:

Safety vent latch to meet ASTM F2090-2008 requirements

### **COLOR OPTIONS:**







NOTE: Colors shown are close approximations and may not be accurate representations for color matching. Please request color swatches from your Plv Gem sales representative to do so.









# **TECTVIEW EX VINYL**







### STANDARD FEATURES

- 3 ¼" jamb depth
- Light Commercial rating and DP 50 available in Single Hung, Single Slider and Picture Window (Specify when ordering)
- Equal site lines on all operating windows
- Superior styling for the look of wood without the maintenance
- Integral J-channel for siding applications and superior frame strength
- Exterior glazing on all EX windows
- ¾" Caldwell adjustable stainless steel balance system

### OPTIONS

- Sash Limiting Devices
- Can upgrade to 1" insulated glass units
- Full or half screens available on all windows
- Full screen track on picture windows for optional solar screens
- Laminated and triple pane glass available







# **TECTVIEW AC VINYL**





### STANDARD FEATURES

- 2 7/8" jamb depth
- Operating or fixed extended round windows as narrow as 23 ½" wide
- Fiberglass half screen on all operating windows standard
- ½" Caldwell adjustable stainless steel balance system
- Slimmer profile for more visible glass
- Equal site lines on all operating windows
- 2 locks on all windows wider than 23 ¼" wide
- Reinforced center bars

### **OPTIONS**

• Sash Limiting Devices



# **TECTVIEW CA VINYL**







### STANDARD FEATURES

- 3 ¼" jamb depth
- Casement, Fixed Casement and Awning utilize the same frame for equal glass in combination units and uniform appearance
- Truth Hardware and folding handles on all operable units
- Stainless steel hardware available for coastal applications



### STANDARD FEATURES

- Stainless steel mortice lock keepers
- 4 1/8" jamb depth
- Industry leading Amesbury Hardware
- Exterior Key lock standard
- Precision sealed bearings on rollers for a lifetime of smooth operation
- Aluminum roller track
- Color matched threshold
- Steel reinforcement in meeting rail, sash stile, and mortice lock frame side.
- DP50 in new construction and replacement up to 96" x 82" two panel doors.
- 3 panel door and sidelites available



### OPTIONS

- Impact resistant 2 panel door to 96" x 82" in new construction or replacement installation.
- 3 panel door available in XOO, OXO, AND OOX
- Transoms and sidelites available in matching frame





# **TECTVIEW CA VINYL**

# PRODUCT DETAILS




We can custom manufacture any kind of window you need, whether you want windows for a new construction project or to replace the windows in your existing home. Our offerings include single-hung, double-hung, slider, casement, picture and geometric shapes.

### Replacements

Our Replacement windows are made in  $\frac{1}{8}$ " increments to ensure a more custom fit for the homeowner. In the end, we'll make sure your windows fit precisely and securely, so you can be absolutely confident in your Burris windows.

# Window Styles Options



# **Obscure Glass Options**

Burris Windows offers many different styles of obscure glass, which can be used to decoratively separate spaces, yet allow light to pass through. Whether you are trying to decorate an office or conference room door, front door of your home, or an exterior bathroom window we have the right obscure glass for you.

Divided lite options between the glass – standard  $\frac{5}{8}$ " wide flat grid, 1" wide contour grids. 1  $\frac{1}{8}$ " wide simulated divided lites are available on the exterior of the glass.

# Quality is Standard ALL OUR WINDOWS COME STANDARD WITH:

- Double strength glass, Cardinal Lowe 270 and Argon. We also offer Cardinal Lowe 366, for more information on our glass see our website or go to: www.cardinalcorp.com.
- Factory or Field mullions available on all windows and doors.
- Industry Leading Caldwell Stainless Steel Adjustable Constant force balance system on all single and double hungs.
- Extruded interlock in sash and meeting rail of all single hung, double hung and sliding windows.
- Aluminum reinforced meeting rail and lock rail in all single hung, double hung and sliders.

### Colors

All Burris windows and doors available in the three colors white, tan and clay with color-matched hardware.



# Efficiency

All Burris Windows can be ordered to meet ENERGY STAR® requirements in all 50 states.



# WINDOR SYSTEMS

# **2750 FOLDING WINDOW**



# WINDOR SYSTEMS

For the Name and the Products You Should Trust!











# WINDOR SYSTEMS

# **2750 FOLDING WINDOW**

# 2750 Bi-Folding Window System



### Features and Benefits

- Vinyl Frame with aluminum reinforcement
- Foam backed seal on main frame
- Contemporary style vinyl sash
- Welded sash corners
- Dual interlocking weather seal on sash for superior air and thermal performance
- Centor™ E3 hardware system in stainless and dark powder coat finishes
- Stainless multipoint locking hardware
- Internal Multipoint shoot bolt system

### Sizes

 New Construction / Replacement Custom applications

### Glass Options

- Cardinal™ 366® LoE Dual Glaze tempered with warm edge spacer system
- Clear, obscure, and custom glass is available

### Hardware

 Hardware Colors; White, Black powder coat, and Brushed Chrome


### Grids

- SDL (Simulated Divided Lite)
- Flat (Colonial)
- Sculptured (Continental)











Win-Dor is a proud member of the following





www.windorsystems.com



**AVAILABLE THROUGH** 







# PREMIUM VINYL COASTAL WINDOWS





PREMIUM VINYL COASTAL WINDOWS



IMPACT ZONE CERTIFIED MISSILE D & HVHZ

**IMPRESSIVE INSIDE & OUT** 





# PREMIUM VINYL COASTAL WINDOWS



# Tested and Certified for Coastal Living.



### HVHZ CERTIFIED

Select window and patio door sizes are certified for High-Velocity Hurricane Zones (HVHZ), meeting the highest impact standards set by the Florida Building Commission for Miami-Dade and Broward County.



### MISSILE D CERTIFIED

Meets Missile D impact specifications for the Florida Building Commission and the Texas Department of Insurance evaluation for the Texas Coast.



<sup>\*</sup> StormBreaker Plus windows and patio doors have SafePoint Max or Max+ impact-resistant glass required for your certification level, style and product size.

# PREMIUM VINYL COASTAL WINDOWS





# The Strength is in the Design.

Simonton StormBreaker Plus® windows deliver the coastal performance your home requires, along with essential features that enhance your home's comfort, aesthetics and convenience.

### SIMONTON STORMBREAKER PLUS

DOUBLE HUNG

### 1. BUILT-IN STRENGTH

Fusion-welded frame and sash increase weather resistance and durability, while the reinforced profiles add to the window's structural integrity.

### 2. BEAUTIFUL DESIGN

Timeless beveled frame design complements any home.

### 3. STORM PROTECTION

SafePoint® Max impact-resistant laminated glass protects against high winds and windborne debris.\*

### 4. ENERGY EFFICIENT

1" insulating glass unit with ProSolar® Low-E glass and Argon gas increases efficiency and comfort.

### 5. LONG-LASTING BEAUTY

The vinyl color is molded throughout the profile for long-lasting beauty that withstands coastal conditions that won't rot, deteriorate, pit or peel like wood or aluminum windows.

### 6. WATER BARRIER

Triple-stepped, sloped Simonton Sill® and Lap Lok® meeting rail on Double Hung windows protect against wind and rain.

### 7. TROUBLE-FREE OPERATION

The stainless-steel constant force coil spring balance system easily raises and lowers the sash



<sup>\*</sup> StormBreaker Plus windows have SafePoint Max or Max+ impact-resistant glass required for certification level and product size.



# PREMIUM VINYL COASTAL WINDOWS

# Select Your Design Options.

Bring your vision to life with a variety of colors and hardware options to complete the aesthetic of your home. StormBreaker Plus® windows and doors are built with virtually maintenance-free vinyl that provides long-lasting beauty and withstands harsh coastal conditions.

### INTERIOR/EXTERIOR VINYL COLORS



### **CUSTOM EXTERIOR FINISHES**




### **HARDWARE FINISHES**





Due to limitations in the printing process, actual colors may vary from printed materials. Please see a sample of the product before making your final color selection.









# PREMIUM VINYL SUNROOM WINDOWS





### A ROOM IS BORN.

Transform your porch, patio or other outdoor living space into an inviting, sun-filled room that you'll enjoy all year long. Simonton windows are the perfect choice for a sunroom that provides maximum enjoyment season after season. A generous selection of styles and sizes allows you to choose the windows that will complement your home beautifully.

Contact your Simonton representative to learn more.



ProSolar\* Low E glass

with an Argon gas fill

provides great energy

to retain cooled air in

warmer months.

efficiency while helping

### Simonton ProFinish® **Contractor Series**

- Premium vinyl construction is
- A sleek, 2 7/8" narrow frame provides an attractive, streamlined appearance.
- An exclusive Lap-Lok\* meeting rail overlaps and interlocks the sash to virtually eliminate air and water infiltration.
- The extruded lift rail is easy to grasp and remarkably durable.
- The sloped sill design forces water away from the window quickly.
- A 20-year Limited Warranty covers screens, hardware and glass. Vinyl is covered by a Lifetime Limited Warranty.
- Easy to install in 2" or 3" aluminum frames.













Our most advanced Low E glass, optional

ProSolar\* Shade is a spectrally selective glass that blocks damaging UV rays while allowing desirable light into the home. The unique formula with three layers of silver helps provide solar heat control, fade protection, visibility and energy savings

### Simonton Reflections® 5500 Series

- Premium vinyl construction requires virtually no maintenance.
- A classic 3 1/4" frame is as durable as it is beautiful
- An exclusive Lap-Lok\* meeting rail overlaps and interlocks the sash to virtually eliminate air and water infiltration.
- The **extruded pull stile** is easy to grasp and won't loosen or break off over time.
- A Double Lifetime Limited Warranty includes vinyl, hardware, screens and glass.
- Easy to install in  $3^{\prime\prime}$  or  $4^{\prime\prime}$









### Styles









### SIMONTON HAS TAKEN THE GUESSWORK OUT OF GLASS.



Order Simonton's regionally specific ENERGY STAR® glass packages to meet the guidelines for the Southern and South-Central regions.



**ENERGY STAR** Regions

South-Central

Southern

Publication No. 080592



# VELUX®











#### SOLAR POWERED FRESH AIR SKYLIGHT

## Solar Powered Fresh Air Skylight VCS Model

The VELUX Solar Powered Fresh Air Skylight uses the power of the sun to refresh your home with the touch of a button.

- Solar-powered battery control system easily opens and closes skylight with remote or smartphone app
- Rain sensor automatically closes skylight at the first sign of rain
- · Safety Glass standard on all VCS models



More Information

Standard Sizes	2222	2234	2246	3030	3046	3434	3737	4622	4630	4646
0°-60° 0:12-20:12										
Outside Curb (W-in. x H-in.)	25½ x 25½	25 ½ x 37 ½	25 ½ x 49 ½	33 ½ x 33 ½	33 ½ x 49 ½	37 ½ x 37 ½	40 ½ x 40 ½	49 ½ x 25 ½	49 ½ x 33 ½	49 ½ x 49 ½



Add a pre-installed solar-powered shade




Smartphone control and automation available



#### **ELECTRIC FRESH AIR SKYLIGHT**







#### **ELECTRIC FRESH AIR SKYLIGHT**

### Electric Fresh Air Skylight VCE Model

The ideal daylighting solution for abundant natural light and fresh air at the touch of a button.

- · Concealed motor and control system easily opens and closes skylight with a remote
- · Rain sensor automatically closes skylight at the first sign of rain
- · Compatible with VELUX skylight shades for ultimate light control
- · Safety Glass is standard on all VCE models



#### More Information

Standard Sizes	2222	2234	2246	3030	3046	3434	4646
0° - 60° 0:12 - 20:12							
Outside Curb (W-in. x H-in.)	25 ½ x 25 ½	25 ½ x 37 ½	25 ½ x 49 ½	33 ½ x 33 ½	33 ½ x 49 ½	37 ½ x 37 ½	49 ½ x 49 ½



solar-powered shade




Add a pre-installed Smartphone control and automation available



### MANUAL FRESH AIR SKYLIGHT









## Manual Fresh Air Skylight VCM Model

Create a healthier home with just the right balance of daylight and fresh air.

- · Manually open and close the skylight with smooth-turning handles or control rods
- · White frames and sashes create a sleek, high quality finish
- · Safety Glass is standard on all VCM models



More Information

Standard Sizes	2222	2234	2246	3030	3046	3434	4646
0°-60° 0:12-20:12							
Outside Curb (W-in.xH-in.)	25 ½ x 25 ½	25 ½ x 37 ½	25 ½ x 49 ½	33 ½ x 33 ½	33 ½ x 49 ½	37 ½ x 37 ½	49 ½ x 49 ½



solar-powered shade




Add a pre-installed Smartphone control and automation available

### **VELUX®**

#### **FIXED SKYLIGHT**







## Fixed Skylight FCM Model

Visually expand your space and transform your home with natural light and sky views.

- Low profile creates a clean, streamlined appearance on the roof
- · Twice the natural light as vertical windows
- · Safety Glass is standard on all FCM models



#### **More Information**

Standard Sizes	1430	1446	2222	2230	2234	2246	2270
0°-60° 0:12-20:12							
Outside Curb (W-in.xH-in.)	17½x 33½	17½ x 49½	25½x 25½	25 ½x 33 ½	25½x 37½	25 ½ x 49 ½	25½x 73½
Standard Sizes	3030	3046	3055	3434	3446	4646	4672



Add a pre-installed solar-powered shade




Smartphone control and automation available



#### **TOUCH REMOTE CONTROLS**





# Simple control of all VELUX skylights and shades with one remote.

The Touch remote controls both skylights and shades, featuring ventilation timing and programmable presets.

We believe it should be easier to create your perfect home environment with VELUX skylights and shades. Now, with VELUX Touch, you only need to reach for one remote to take control of every skylight and shade you install. Talk about indoor comfort right at your fingertips!


- · Remote operation in room where your skylights are installed
- · Operate multiple products at once
- $\cdot$  Group skylights and shades to operate together
- $\cdot$  Set the ventilation timer for regular automated home airing
- $\cdot\,$  Lock home option to securely close all your skylights automatically
- · Preset shade and skylight positions for even easier operation

More Information



### **VELUX®**

#### **TOUCH REMOTE CONTROLS**



#### Remote Comparison











#### **VELUX Wall Switch**

#### VELUX Touch

For customers that want basic and simple benefits, and no smartphone control.

#### VELUX App Control

For customers that wish for more benefits and smartphone control, without full automation of products.

#### VELUX ACTIVE


For customers that wish to see insight into air and temperature statistics of their home and improve it through automatic ventilation and heat control.

Price	Included with Product	\$	\$	\$\$
Remote Operation Inside the Room	✓	$\checkmark$	✓	$\checkmark$
Remote Operation from Anywhere			✓	✓
Operation of Multiple Products		✓	✓	✓
Requires Wi-Fi Connection			✓	✓
Compatible with Apple HomeKit <sup>®</sup> and Google Assistant <sup>™</sup>			<b>√</b>	<b>√</b>
Group Products		✓	✓	✓
Ventilation Timer		✓	✓	✓
Lock Home Option (close all skylights)		✓	✓	✓
Accessible to All Household Members	✓	✓	✓	✓
Scheduling to Personal Preferences			✓	✓
Voice Control			✓	✓
Sensor-based Automation				✓
Use of Weather Data				✓
Live Indoor Sensor Data				✓










## Three Layers of Water Protection

At VELUX, we've developed three layers of water protection to safeguard your house against damaging leaks. The VELUX Skylight System carries a 10-year installation warranty, plus 20 years on glass, 10 years on product, and 5 years on shades and controls.



Rest easily underneath your skylight knowing that it will never let in rain or moisture.

- Pre-attached Gasket provides a tight outer seal for leak-proof installation.
- 2 Adhesive Underlayment provides secondary water protection in harsh weather conditions.
- 3 Engineered Flashing provides primary water protection and allows for easy installation.





#### **COMPLETE LIGHT CONTROL**

## Complete light control.

#### Solar-Powered Shade Pairing

VELUX shades allow you to control the light, enhance your decor, and improve energy efficiency.

We offer the option of ordering VELUX Solar Powered Fresh Air Skylights with **Pre-Installed White Room Darkening, Double-Pleated shades**.

- · Room darkening, double-pleated shade
- · Blackout cloth, honeycomb structure
- · Neat pleats

**In-Stock Shade**<sup>1</sup> Free factory installation Room-Darkening Double-Pleated



More Information

White

## **Special Order**<sup>2</sup> Ships seperately from skylight Room-Darkening Double-Pleated



#### Light-Filtering Single-Pleated



¹ In-Stock: Available for factory installation, 2-4 business days. Custom sizes must be placed as special order. ² Special Order. Not available for factory installation. Shades ship separately from your skylight, 14 business days.





#### **QPF SELF-FLASHED FIXED SKYLIGHT**



## QPF

## Self-Flashed Fixed Skylight

The VELUX Fixed Self-Flashed Skylight is a daylighting alternative to skylights with traditional flashing methods. This skylight features a pre-installed metal self-flashing to provide a leak-free installation and designed to be used on thin roofing materials. Additionally, with its clean exterior profile, this skylight provides uninhibited bright natural light to the space below.

**Ideal Applications:** 

Out of reach <u>entry ways</u>, <u>living rooms</u> and <u>bedrooms</u> that can benefit from daylight.

#### **FEATURES & BENEFITS**

- Clean exterior profile provides natural light without obstructing roofline
- Versatile sizing allows for greater flexibilityin positioning options
- Seamlessly pairs with any VELUX shades for optimal light control select shades can be pre-installed for free
- Eligible for Federal Solar Tax Credit\* with the addition of Solar Shades

#### PRODUCT DETAILS

- Laminated LoE3 Glass: double-paned argon-gas-filled LoE3 glass that provides
  excellent energy performance for year round comfort. Plus, it includes the
  added safety of laminated glass, which building codes require for out-of-reach
  applications.
- Pre-finished white painted frames
- 10 year hail with Clean, Quiet & Safe glass

#### **OPTIONAL SKYLIGHT UPGRADES**

- Impact Glass
- White Laminated Glass
- Tempered LoĒ



#### **ACCESSORIES**

 Factory pre-installed Room-Darkening or Light Filtering shades







veluxusa.com

\*For more information visit veluxusa.com/taxcredit.


V5065-0921 ©2021 VELUX Group. \*VELUX, VELUX logo are registered trademarks.





#### **QPF SELF-FLASHED FIXED SKYLIGHT**


## **Self-Flashed Fixed** Skylight



#### **COMPLIANCE AND CERTIFICATIONS**

- DBPR Florida
- IAPM0

- NFRC, National Fenestration Rating Council
- WDMA, Window & Door Manufacturing Association



<u>veluxusa.com</u>
\*For more information visit <u>veluxusa.com/taxcredit</u>.

©2021 VELUX Group. \*VELUX, VELUX logo are registered trademarks.



#### **FX DOUBLE DOME SKYLIGHT**



#### **FX** Double Dome Skylight **Technical Product Data Sheet**

#### Description

FX Fixed Curb Mount Double Dome Skylight that mounts to a site-built curb (residential curbs typically 2x4 or 2x6). Fixed skylight, provided with various acrylic glazings, is manufactured with a mill finish aluminum frame. Integral inner frame/gasket prevents air and water infiltration while allowing the removal of interior condensation.

#### Installation

- No designated top, bottom, or sides for installation in any direction.
- Mill finish exterior frame.
- Encapsulated inner frame is 100% thermally broken.
- O degrees to 60 degrees, use standard installation procedure.

#### Interior Accessories

None

#### Standard Sizes

• 2222, 2246, 3030, 3434, 4646

#### Special Sizes

Custom sizes with widths from 17" to 102" and heights from 17" to 150"



#### Warranty

• Skylight - 5 years from the date of purchase; VELUX warrants that the skylight will be free from defects in material and workmanship.

#### **Flashings**

- ECL Engineered flashing for single installation with thin roofing material (1/2" max) for roof pitch from 10-60 degrees.
- ECW Engineered flashing for single installation with tile roofing material (over 3/4") for roof pitch from 14-60 degrees.

#### Glazings

Acrylic white over clear		0A2A1	
Size	Inside Curb	Outside Curb	Max Skylight Clearance
2222	22-1/2" x 22-1/2"	25-1/2" x 25-1/2"	26-11/16" x 26-11/16"
2246	22-1/2" x 46-1/2"	25-1/2" x 49-1/2"	26-11/16" x 50-11/16"
3030	30-1/2" x 30-1/2"	33-1/2" x 33-1/2"	34-11/16" x 34-11/16"
3434	34-1/2" x 34-1/2"	37-1/2" x 37-1/2"	38-11/16" x 38-11/16"
4646	46-1/2" x 46-1/2"	49-1/2" x 49-1/2"	50-11/16" x 50-11/16"

Ourton Circa (OO)	Width	17" to 102"
Custom Sizes (OC)	Height	17" to 150"

Minimum OC 17"w x 17"H

Consult with Customer Service for special glazing options.



### **VELUX®**

#### **QX DOUBLE DOME SKYLIGHT**

## **QX** Double Dome Skylight Technical Product Data Sheet

#### Description

 QX pan flashed Double Dome Skylight that mounts to a residential roof deck. Fixed skylight, provided with acrylic glazings, is manufactured with a mill finish aluminum frame. Integral inner frame/gasket prevents air and water infiltration while allowing the removal of interior condensation.

#### Installation

- No designated top, bottom, or sides for installation in any direction.
- Mill finish exterior frame.
- Encapsulated inner frame is 100% thermally broken.
- 10 degrees to 60 degrees, use standard installation procedure.

#### Flashings

N/A

#### Interior Accessories

• None

#### Type Sign

- Example QX 2222 0A2A1 01BM05
- · Tag on exterior frame.

#### **Standard Sizes**

• 2222, 2246

#### Special Sizes

· No custom sizes





#### Warranty

 Skylight – 5 years from the date of purchase; VELUX warrants that the skylight will be free from defects in material and workmanship.

#### Glazings

Acrylic white over clea	0A2A1	

Size	Rough Opening	Outside Flashing
2222	22-1/2" x 22-1/2"	28-5/8" x 28-5/8"
2246	22-1/2" x 46-1/2"	28-5/8" x 52-5/8"

Consult with Customer Service for special glazing options.



MM090224WC